




NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

NASA CR-

134413



(NASA-CR-134413) WIND TUNNEL TESTS OF THE
0.010-SCALE SPACE SHUTTLE INTEGRATED VEHICLE
(MODEL 52-QT) IN THE NASA/AMES 3.5-FOOT
HYPERSONIC WIND TUNNEL (IA18) (Chrysler
Corp.) 115 p HC \$5.25

N7D-19335

Uncias
CSCL 22B G3/18 14453

SPACE SHUTTLE

AEROTHERMODYNAMIC DATA REPORT

JOHNSON SPACE CENTER

HOUSTON, TEXAS

DATA MANAGEMENT SERVICES

SPACE DIVISION



CHRYSLER
CORPORATION

March, 1975

DMS-DR-2160
NASA CR-134,413

WIND TUNNEL TESTS OF THE 0.010-SCALE
SPACE SHUTTLE INTEGRATED VEHICLE (MODEL 52-0T) IN
THE NASA/AMES 3.5-FOOT HYPERSONIC WIND TUNNEL
(IA18)

By

V. Esparza, E. Chee and J. Stone
Rockwell International Space Division
J. A. Mellenthin
NASA/Ames Research Center

Prepared under NASA Contract Number NAS9-13247

by

Data Management Services
Chrysler Corporation Space Division
New Orleans, La. 70189

for

Engineering Analysis Division

Johnson Space Center
National Aeronautics and Space Administration
Houston, Texas

WIND TUNNEL TEST SPECIFICS:

Test Number: ARC 3.5-191
NASA Series Number: IA18
Model Number: 52-0T
Test Dates: 9 through 12 April 1974 - Occupancy Hours: 62

FACILITY COORDINATOR:

Joseph Marvin
Mail Stop 229-1
Ames Research Center
Moffett Field, California 94035 Phone: (415) 965-5390

PROJECT ENGINEERS:

V. Esparza and E. Chee
Rockwell International
Space Division
Mail Code AC07
12214 Lakewood Blvd.
Downey, California 90241

Phone: (213) 922-2974

AERODYNAMICS ANALYSIS ENGINEER:

J. S. Stone
Rockwell International
Space Division
Mail Code AC07
12214 Lakewood Blvd.
Downey, California 90241

Phone: (213) 922-4831

J. A. Mellenthin
Ames Research Center
Mail Stop N-229-1
Moffett Field, California 94035

Phone: (415) 965-6211

DATA MANAGEMENT SERVICES:

Prepared by: Liaison--D. A. Sarver, T. L. Mulkey
Operations--B. J. Burst

Reviewed by: J. L. Glynn *jb.*

Approved:

N. D. Kemp
N. D. Kemp, Manager
Data Management Services

Concurrence:

J. G. Swider
J. G. Swider, Manager
Flight Technology Branch

Chrysler Corporation Space Division assumes no responsibility for the data presented other than display characteristics.

WIND TUNNEL TESTS OF THE 0.010-SCALE
SPACE SHUTTLE INTEGRATED VEHICLE (MODEL 52-OT)
IN THE NASA/AMES 3.5-FOOT HYPERSONIC WIND TUNNEL (IA18)

By V. Esparza, E. Chee and J. Stone, Rockwell International Space Division
J. A. Mellenthin, NASA/Ames Research Center

ABSTRACT

Experimental aerodynamic investigations were conducted in the NASA/Ames Research Center 3.5-foot Hypersonic Wind Tunnel from April 9, 1974 to April 12, 1974 on an 0.010-scale model of the Space Shuttle Integrated Vehicle consisting of an orbiter and external tank (Model 52-OT).

The purpose of the test was to evaluate the basic hypersonic stability characteristics of the orbiter attached rigidly to the external tank and to evaluate the basic hypersonic stability characteristics of external tank alone simulating RTLS abort conditions. Test IA18 was conducted at Mach numbers of 5.3, 7.3 and 10.3.

The integrated vehicle was tested at angles of attack from -8° through $+30^\circ$ and angles of sideslip of -8° through $+8^\circ$ at fixed angles of attack of -4° , 0° , and $+4^\circ$. A maximum angle-of-attack range of $+15^\circ$ through $+40^\circ$ was obtained for this configuration, at Mach number 7.3, for one run only.

External tank alone testing was conducted at angles of attack from $+8^\circ$ through -30° and angles of sideslip of -8° through $+8^\circ$ at fixed angles of attack of -4° , 0° and $+4^\circ$.

Six-component force data and static base pressures were recorded during the test.

TABLE OF CONTENTS

	Page
ABSTRACT	111
INDEX OF MODEL FIGURES	2
INDEX OF DATA FIGURES	3
NOMENCLATURE	5
CONFIGURATIONS INVESTIGATED	9
TEST FACILITY DESCRIPTION	11
DATA REDUCTION	12
TABLES	
I. TEST CONDITIONS	14
II. DATASET/RUN NUMBER COLLATION SUMMARY	15
III. MODEL DIMENSIONAL DATA	16
FIGURES	
MODEL	42
DATA	51
APPENDIX	
TABULATED SOURCE DATA	

INDEX OF MODEL FIGURES

Figure		Page
1.	Axis Systems	42
2.	Model Sketches	
a.	Integrated Configuration - 0g T20	43
b.	Orbiter - 0g	44
c.	External Tank (T20) per R. I. Drawing VL78-000062B	45
d.	Base Pressure Orifice Locations	46
3.	Model Installation Photographs	
a.	Orbiter and Tank, Side View	47
b.	Orbiter and Tank, 3/4 Rear View	48
c.	Tank Only, Rolled 90° for Sideslip Run, 3/4 Rear View from Right Side	49
d.	Tank Only, Rolled 90° for Sideslip Run, Left Side View (Top of Model is toward Viewer)	50

INDEX OF DATA FIGURES

FIGURE NUMBER	TITLE	COEFFICIENT SCHEDULE	CONDITIONS VARYING	PLOT PAGES
4	Effect of Mach Number on Second Stage Longitudinal Aerodynamic Characteristics	A	MACH	1-12
5	Effect of Mach Number on Isolated ET Longitudinal Aerodynamic Characteristics	A	MACH	13-16
6	Effect of Angle of Attack on Second Stage Lateral-Directional Aerodynamic Characteristics	B	ALPHA	17-28
7	Effect of Angle of Attack on Isolated ET Lateral-Directional Aerodynamic Characteristics	H	ALPHA	29-37
8	Summary of Second Stage Longitudinal Aerodynamic Characteristics	C	MACH	38-38
9	Summary of Isolated ET Longitudinal Aerodynamic Characteristics	D	MACH	39-39
10	Summary of Second Stage Lateral-Directional Aerodynamic Characteristics	E	MACH, ALPHA	40-40
11	Summary of Isolated ET Lateral-Directional Aerodynamic Characteristics	F	MACH, ALPHA	41-41
12	Summary of Second Stage Longitudinal Characteristics With Beta Varying	G	MACH, BETA	42-44
13	Summary of Isolated ET Longitudinal Characteristics With Beta Varying	G	MACH, BETA	45-47

INDEX OF DATA FIGURES (Concluded)

COEFFICIENT SCHEDULE:

- (A): CAF, CN, CLM vs ALPHA,
CN vs CLM
- (B): CY, CYN, CBL vs BETA,
CY vs CYN
- (C): CAFAFO, CNAFO, CLMAFO, XAC/L vs MACH
- (D): CAFAFO, CLMAFO, XAC/L vs MACH
- (E): CYBETA, CBLBET, CYNBET, YAC/L vs MACH
- (F): CYBETA, CYNBET, YAC/L vs MACH
- (G): CAF, CN, CLM, XAC/L vs MACH
- (H): CY, CYN vs BETA
CY vs CYN

NOMENCLATURE
General

<u>SYMBOL</u>	<u>SADSAC SYMBOL</u>	<u>DEFINITION</u>
a		speed of sound; m/sec, ft/sec
C _p	CP	pressure coefficient; $(p_1 - p_\infty)/q$
M	MACH	Mach number; V/a
P		pressure; N/m ² , psf
q	Q(NSM) Q(PSF)	dynamic pressure; $1/2\rho V^2$, N/m ² , psf
RN/L	RN/L	unit Reynolds number; per m, per ft
V		velocity; m/sec, ft/sec
α	ALPHA	angle of attack, degrees
β	BETA	angle of sideslip, degrees
ψ	PSI	angle of yaw, degrees
ϕ	PHI	angle of roll, degrees
ρ		mass density; kg/m ³ , slugs/ft ³

Reference & C.G. Definitions

A _b		base area; m ² , ft ²
b	BREF	wing span or reference span; ft
c.g.		center of gravity
$\frac{l}{c}$ _{REF}	LREF	reference length or wing mean aerodynamic chord; m, ft
S	SREF	wing area or reference area; m ² , ft ²
	MRP	moment reference point
	XMRP	moment reference point on X axis
	YMRP	moment reference point on Y axis
	ZMRP	moment reference point on Z axis

SUBSCRIPTS

b	base
l	local
s	static conditions
t	total conditions
∞	free stream

NOMENCLATURE (Continued)

Body-Axis System

SYMBOL	SADCAC SYMBOL	DEFINITION
c_N	CN	normal-force coefficient; $\frac{\text{normal force}}{qS}$
c_A	CA	axial-force coefficient; $\frac{\text{axial force}}{qS}$
c_Y	CY	side-force coefficient; $\frac{\text{side force}}{qS}$
c_{A_b}	CAB	base-force coefficient; $\frac{\text{base force}}{qS}$ $-A_b(p_b - p_\infty)/qS$
c_{A_f}	CAF	forebody axial force coefficient, $c_A = c_{A_b}$
c_m	CIM	pitching-moment coefficient; $\frac{\text{pitching moment}}{q\bar{S}_{REF}}$
c_n	CYN	yawing-moment coefficient; $\frac{\text{yawing moment}}{q\bar{S}_b}$
c_l	CBL	rolling-moment coefficient; $\frac{\text{rolling moment}}{q\bar{S}_b}$

Stability-Axis System

c_L	CL	lift coefficient; $\frac{\text{lift}}{qS}$
c_D	CD	drag coefficient; $\frac{\text{drag}}{qS}$
c_{D_b}	CDB	base-drag coefficient; $\frac{\text{base drag}}{qC}$
c_{D_f}	CDF	forebody drag coefficient; $c_D = c_{D_b}$
c_Y	CY	side-force coefficient; $\frac{\text{side force}}{qC}$
c_m	CIM	pitching-moment coefficient; $\frac{\text{pitching moment}}{q\bar{S}_{REF}}$
c_n	CIN	yawing-moment coefficient; $\frac{\text{yawing moment}}{q\bar{S}_b}$
c_l	CBL	rolling-moment coefficient; $\frac{\text{rolling moment}}{q\bar{S}_b}$
L/D	L/D	lift-to-drag ratio; c_L/c_D
L/D_f	L/D _f	lift-to-forebody-drag ratio; c_L/c_{D_f}

NOMENCLATURE (Continued)
Additions to Standard List

<u>Symbol</u>	<u>Plot Symbol</u>	<u>Definition</u>
A _i		model base area at station i, i=1, ..., 10, in ²
C _{P1}		Orbiter OMS pod base pressure coefficient
C _{P3}		Orbiter base pressure coefficient
C _{P5}		external tank base pressure coefficient in the integrated configuration
C _{P6}		external tank base pressure coefficient
C _{P7}		external tank base pressure coefficient
C _{P10}		Orbiter balance cavity pressure coefficient
C _{P5}		external tank balance cavity pressure coefficient (tank alone)
C _{A_b0}	CAB-0	Orbiter base axial force coefficient
C _{A_bOET}	CAB-T	external tank base axial-force coefficient in the integrated configuration
C _{A_bET}	CAB-T	external tank base axial-force coefficient for tank alone
(C _N) _{$\alpha=0$}	CNAFO	normal-force coefficient at $\alpha=0$
(C _M) _{$\alpha=0$}	CLMAFO	pitching-moment coefficient at $\alpha=0$
(C _{N_{α}})	CNALFA	normal-force coefficient slope ($-5^\circ \leq \alpha \leq 5^\circ$)
C _{m_{α}}	CLMALF	pitching-moment coefficient slope ($-5^\circ \leq \alpha \leq 5^\circ$)
X _{m_{AC}} /R	XAC/L	aerodynamic center, pitch ($-5^\circ \leq \alpha \leq 5^\circ$)

NOMENCLATURE (Concluded)
Additions to Standard List

<u>Symbol</u>	<u>Plot Symbol</u>	<u>Definition</u>
$C_{Y\beta}$	CYBETA	side-force coefficient slope ($-5^\circ \leq \beta \leq 5^\circ$)
C_{ℓ_β}	CBLBET	rolling-moment coefficient slope ($-5^\circ \leq \beta \leq 5^\circ$)
C_{n_β}	CYNBET	yawing-moment coefficient slope ($-5^\circ \leq \beta \leq 5^\circ$)
$X_{n_{AC}}/\ell_R$	YAC/L	aerodynamic center, yaw ($-5^\circ \leq \beta \leq 5^\circ$)
$(C_{A_f})_{\alpha=0}$	CAFAFO	forebody axial force coefficient at $\alpha=0$

CONFIGURATIONS INVESTIGATED

The model for this test was an 0.010-scale representation of the Space Shuttle Integrated Configuration (model 52-0T). The model consisted of the orbiter and external tank. The model was constructed of stainless steel.

There were two configurations tested. The first configuration tested was the orbiter rigidly attached to the external tank. The second configuration tested was external tank alone. Model components tested were:

$$O_9 = B_{19} C_7 E_{23} F_5 M_4 N_8 N_{24} R_5 V_7 W_{107}$$

Orbiter

B_{19} = VL70-000139B (1ines) body

C_7 = VL70-000139B (1ines) canopy

E_{23} = VL70-000139B (1ines) elevon

F_5 = VL70-000139B (1ines) Bodyflap

M_4 = VL70-000139B (1ines) OMS pod

N_8 = VL70-000140A (1ines) OMS nozzle

N_{24} = VL70-000140A (1ines) main engine nozzle

R_5 = VL70-000139B and VL70-000095 rudder

V_7 = VL70-000139B (1ines) vertical tail

W_{107} = VL70-000139B (1ines) wing

External Tank

T_{20} = VL78-000062B (1ines) external tank

CONFIGURATIONS INVESTIGATED (Concluded)

AT₁₆ = VL78-000062B, SK-H-4011; forward Orbiter/ ET attach structure
(when attached to Orbiter)

AT₁₇ = VL78-000062B, SK-H-4013; left rear Orbiter/ET attach structure

AT₁₈ = VL78-000062B, SK-H-4013; right rear Orbiter/ET attach structure

AT₁₉ = VL78-000062B, VL72-000140, VL72-000115; forward SRB/ET attach structure

AT₂₀ = VL78-000062B, VL72-000140, VL72-000115; Aft SRB/ET attach structure

AT₂₄ = VL78-000062B, forward Orbiter/ET attach structure (tank alone)

FL₅ = VL78-000062B, LOX feed line simulated between ET and Orbiter

FL₆ = VL78-000062B pressure line; max cross-sectional area simulating LH₂ pressure line and electrical conduit box on the ET.

FL₉ = VL78-000062B umbilical feedline

FR₆ = VL78-000062B VL78-000050 cross-members between ET/Orbiter attach structure

PT₁₂ = VL78-000062B lightning rod attached to ET

PT₁₃ = VL78-000062B ET protuberance simulation of LOX recirculation line and electrical conduit box

PT₁₄ = VL78-000062B ET protuberance simulation LOX pressure line

PT₁₉ = VL78-000062B SRB separation push off pad

PT₂₀ = VL78-000062B nose cone lines

TEST FACILITY DESCRIPTION

The NASA-Ames 3.5-Foot Hypersonic Wind Tunnel is a closed-circuit, blowdown-type tunnel capable of operating at nominal Mach numbers of 5, 7, and 10 at pressures to 1800 psia and temperatures to 3400°R for run times to four minutes. The major components of the facility include a gas storage system where the test gas is stored at 3000 psi, a storage heater filled with aluminum-oxide pebbles capable of heating the test gas to 3400°R, axisymmetric contoured nozzles with exit diameters of 42 inches for generating the desired Mach number, and a 900,000 ft³ vacuum storage system which operates to pressures of 0.3 psia. The test section itself is an open-jet type enclosed within a chamber approximately 12-feet in diameter and 40-feet in length, arranged transversally to the flow direction.

A model support system is provided that can pitch models through an angle-of-attack range of -20 to +20 degrees, in a vertical plane, about a fixed point of rotation on the tunnel centerline. This rotation point is adjustable from 1 to 5 feet from the nozzle exit plane. The model normally is out of the test stream (strut centerline 37-inches from tunnel centerline) until the tunnel test conditions are established after which it is inserted. Insertion time is adjustable to as little as 1/2 second and models may be inserted at any strut angle.

A high-speed, analog-to-digital data acquisition system is used to record test data on magnetic tape. The present system is equipped to measure and record the outputs from 80 transducers in addition to 20 channels of tunnel parameters.

DATA REDUCTION

The aerodynamic force data presented were measured by the Task 1.0-inch MK XIV strain gage balance and the moment data were transferred to the external tank centerline at a point 6.501 inches (model scale) aft of the tank nose.

Base pressure axial-force coefficients were calculated for the individual regions as follows:

1. Orbiter base axial-force coefficient:

$$C_{A_b} = -[A_1 C_{P_1} + A_3 C_{P_3} + A_{10} C_{P_{10}}]/S$$

where: $A_1 = A_1 + A_2 = 2.64 \text{ in}^2$

$$A_3 = A_3 + A_4 = 3.28 \text{ in}^2$$

$$A_{10} = 0.843 \text{ in}^2$$

2. External tank (when in the integrated configuration)

$$C_{A_b} = -[A_5 C_{P_5} + A_6 C_{P_6} + A_7 C_{P_7}]/S$$

where: $A_5 = 1.767 \text{ in}^2$

$$A_6 = 1.699 \text{ in}^2$$

$$A_7 = 5.097 \text{ in}^2$$

3. External tank (alone)

$$C_{A_b} = -[A_5 C_{P_5} + A_6 C_{P_6} + A_7 C_{P_7}]/S$$

where: $A_5 = \text{sting cavity} = 1.109 \text{ in}^2$

$$A_6 = 1.699 \text{ in}^2$$

$$A_7 = 5.097 \text{ in}^2$$

DATA REDUCTION (Concluded)

The following reference dimensions were used for data reduction:

<u>Symbol</u>	<u>Definition</u>	<u>Value</u> (model scale)
S	reference area	38.736 in ²
XMRP	longitudinal moment reference point	9.79 in
YMRP	moment reference point on Y axis	0.00 in
ZMRP	moment reference point on Z axis	4.00 in
l_R	reference length	12.903 in

The location of the base pressure orifices and their respective areas are shown in figure 2d.

TABLE I.

TABLE II.

TEST : 24185444C 3-E, 411
DATA SET/RUN NUMBER COLLATION SUMMARY

DATE : APRIL 11, 1974

DATA SET IDENTIFIER	CONFIGURATION	SCMD.	PARAMETERS/VALUES						NO. OF RUNS	MACH NUMBERS (OR ALTERNATE INDEPENDENT VARIABLE)	
			α	β	C_x	C_y	C_z	R			
SE-CC1	CRBITER + TANK	A	C	C	C	C	C	R	19	1.8	1
SE-C2		B	C	C	C	C	C		22	1.6	3
SE-C3		C	E	C	C	C	C		21	1.4	2
SE-C4		D	O	C	C	C	C		23	1.5	4
SE-C5		E	C	C	C	C	C		17		
SE-C6	TANK	D	C	C	C	C	C		26	9	8
SE-C7		F	B	C	C	C	C		11	6	
SE-C8		G	B	C	C	C	C		25	1.3	7
SE-C9		H	B	C	C	C	C		27	1.2	5
SE-C10	CRBITER + TANK	C	R	C	C	X	C		2C		
SE-C11		I	O	C	C	X	C		19		
SE-C12	TANK	D	C	C	C	X	C		26		
NOTES: * D/S ARE CORRECTED FOR CAB EFFECTS AT MACH 5.3 ONLY; CAB CONSIDERED NEGLIGIBLE FOR REMAINDER OF MACH RANGE. ** D/S CONTAIN DATA (CAB-O, CAB-T) USED TO CORRECT AXIAL FORCE AND PITCHING MOMENT (MATED CONFIG.) COEFFICIENTS AT MACH 5.3. XES010 USED TO CORRECT RES002-004, XES001 USED TO CORRECT RES001, AND XES006 USED TO CORRECT RES008-009. XES006 IS ALPHA SWEEP DATA BUT WAS USED TO CORRECT BOTH α AND β SWEET DATA DUE TO TANK SYMMETRY.											
RES	CAF	CL-M ₁	CYN	CBL ₁							
X:	CAF-S ₁	CL-E ₁	CY ₁	CA ₁	CL-M ₁	CYN ₁	CBL ₁				
TYPE OF DATA α OR β EQUATIONS											
COEFFICIENT SCHEDULES RES: -3, -4, -5, -6, -7, -8, -9, -10, -11, -12, -13, -14, -15, -2C, 25, 3C CAF: -3, -4, -5, -6, -7, -8, -9, -10, -11, -12, -13, -14, -15, -2C, 25, 3C D/S: -3, -4, -5, -6, -7, -8, -9, -10, -11, -12, -13, -14, -15, -2C, 25, 3C											

TABLE III. - MODEL DIMENSIONAL DATA

MODEL COMPONENT : BODY - B19

GENERAL DESCRIPTION : FUSELAGE per Rockwell Lines VL70-000139B

SCALE: 0.010

DRAWING NUMBER VL70-000139B

DIMENSIONS	FULL SCALE	MODEL SCALE
Length - In.	<u>1290.3</u>	<u>12.903</u>
Max Width - In.	<u>267.6</u>	<u>2.676</u>
Max Depth - In.	<u>244.5</u>	<u>2.445</u>
Fineness Ratio	<u>4.82175</u>	<u>4.82175</u>
Area		
Max. Cross-Sectional	<u>386.67</u>	<u>0.0387</u>
Planform		
Wetted		
Base		

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT : CANOPY - C₇

GENERAL DESCRIPTION : Basic configuration 3A canopy

MODEL SCALE: 0.010

DRAWING NUMBER VL70-000139B

DIMENSIONS :

FULL SCALE

MODEL SCALE

Length ($X_0=433$ to $X_0=670$) in.FS 237. 2,370

Max Width

Max Depth

Fineness Ratio

Area

Max. Cross-Sectional

Planform

Wetted

Base

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: ELEVON - E₂₃GENERAL DESCRIPTION: Configuration 3 per W107 Rockwell LinesVL70-000139B, data for (1) of (2) sides.MODEL SCALE: 0.010DRAWING NUMBER: VL70-000139B

<u>DIMENSIONS:</u>	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Area - FT ²	<u>205.52</u>	<u>0.0206</u>
Span (equivalent) - In.	<u>353.34</u>	<u>3.533</u>
Inb'd equivalent chord - In.	<u>114.78</u>	<u>1.148</u>
Outb'd equivalent chord - In.	<u>55.00</u>	<u>0.550</u>
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord	<u>0.208</u>	<u>0.208</u>
At Outb'd equiv. chord	<u>0.400</u>	<u>0.400</u>
Sweep Back Angles, degrees		
Leading Edge	<u>0.00</u>	<u>0.00</u>
Trailing Edge	<u>-10.24</u>	<u>-10.24</u>
Hingeline	<u>0.00</u>	<u>0.00</u>
Area Moment (Normal to hinge line)	<u>1548.07</u>	<u>0.00155</u>

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT : BODY FLAP - F₅

GENERAL DESCRIPTION : Configuration 3 - A lightweight orbiter body flap

MODEL SCALE: 0.010 MODEL DRAWING NO.: SS-A00062

DRAWING NUMBER VL70-000139B

DIMENSIONS	FULL SCALE	MODEL SCALE
Length - In.	<u>84.70</u>	<u>0.8470</u>
Max Width - In.	<u>267.6</u>	<u>2.6760</u>
Max Depth	<u> </u>	<u> </u>
Fineness Ratio	<u> </u>	<u> </u>
Area	<u> </u>	<u> </u>
Max. Cross-Sectional	<u>142.5195</u>	<u>0.01425</u>
Planform	<u> </u>	<u> </u>
Wetted	<u>38.0958</u>	<u>0.00381</u>
Base	<u> </u>	<u> </u>

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT : OMS - M₄

GENERAL DESCRIPTION : Orbital maneuvering system pods located on
the orbiter aft fuselage

MODEL SCALE: 0.010

DRAWING NUMBER VL70-000139

DIMENSIONS	FULL SCALE	MODEL SCALE
Length - In.	<u>346.0</u>	<u>3.460</u>
Max Width - In.	<u>108.0</u>	<u>1.080</u>
Max Depth - In.	<u>113.0</u>	<u>1.113</u>
Fineness Ratio		
Area		
Max. Cross-Sectional		
Planform		
Wetted		
Base		

Centerline of OMS Pods:

$$WP = 463.9 \text{ IN FS: } WP = 400 + 63.9 = 463.9$$

$$BP = 80.0 \text{ IN F.S.}$$

$$\text{Length: } 1214.0 \text{ to } 1560.0 = 346.0 \text{ IN. F.S.}$$

NOTE: M₄ identical to M of 2A configuration except intersection
to body.

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: MPS NOZZLES - N8

GENERAL DESCRIPTION: Basic OMS Nozzle of Configuration 2A per Rockwell
 Lines VL70-008306 and VL70-000089 "B". Intersection of nozzle
 exit plane and nozzle centerline at $X_0 = 1570.75$, $Y_0 = \pm 99.25$,
 $Z_0 = 507.25$

MODEL SCALE: 0.010

DRAWING NUMBER: VL70-008306, VL70-000089 "B", SS-A00092

DIMENSIONS:	FULL SCALE	MODEL SCALE
MACH NO.		
Length - In.		
Gimbal Point to Exit Plane		
Throat to Exit Plane		
Diameter - In.		
Exit	50.00	0.50
Throat	N/A	N/A
Inlet	28.00	0.280
Area - ft ²		
Exit	13.635	0.1364
Throat		
Gimbal Point (Station) - In.		
Upper Nozzle		
X	1518.0	15.18
Y	+ 88.0	+ 0.88
Z	492.0	4.92
Lower Nozzles		
X		
Y		
Z		
Null Position - Deg.		
Upper-Nozzle		
Pitch	15°49'	15°49'
Yaw (Outboard)	+ 12°17'	+ 12°17'

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: MPS NOZZLES - N 24

GENERAL DESCRIPTION: Configuration 140A/B Orbiter MPS Nozzles

MODEL SCALE: 0.010DRAWING NUMBER: VL70-005030A, VL70-000140A

DIMENSIONS:	FULL SCALE	MODEL SCALE
MACH NO.		
Length - In.		
Gimbal Point to Exit Plane	<u>157.0</u>	<u>1.570</u>
Throat to Exit Plane	<u>99.2</u>	<u>0.992</u>
Diameter - In.		
Exit	<u>91.000</u>	<u>0.910</u>
Throat		
Inlet		
Area - ft ²		
Exit	<u>45.16585</u>	<u>0.00452</u>
Throat		
Gimbal Point (Station) - In.		
Upper Nozzle		
X	<u>1445.0</u>	<u>14.450</u>
Y	<u>0</u>	<u>0</u>
Z	<u>443.0</u>	<u>4.430</u>
Lower Nozzles		
X	<u>1468.16996</u>	<u>0.00147</u>
Y	<u>53.0000</u>	<u>0.530</u>
Z	<u>342.63988</u>	<u>3.426</u>
Null Position - Deg.		
Upper Nozzle		
Pitch	<u>16°</u>	<u>16°</u>
Yaw	<u>0°</u>	<u>0°</u>
Lower Nozzle		
Pitch	<u>10°</u>	<u>10°</u>
Yaw	<u>3.5°</u>	<u>3.5°</u>

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: Rudder - R_5 GENERAL DESCRIPTION: Rudder for vertical stabilizer V_7

MODEL SCALE: 0.010

DRAWING NUMBER: VL70-000095

DIMENSIONS:

	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Area - Ft^2	100.15	0.0100
Span (equivalent) - In.	201.0	2.010
Inb'd equivalent chord - In.	91.585	0.916
Outb'd equivalent chord - In.	50.833	0.508
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord	0.400	0.400
At Outb'd equiv. chord	0.400	0.400
Sweep Back Angles, degrees		
Leading Edge	34.83	34.83
Tailing Edge	26.25	26.25
Hingeline	34.83	34.83
Area Moment (Normal to hinge line) FT^3	526.125	0.0005.261

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: VERTICAL - V 7

GENERAL DESCRIPTION: Centerline vertical tail, double-wedge airfoil
with rounded leading edge.NOTE: Same As V₅, but with manipulator housing removed.

MODEL SCALE: 0.010

DRAWING NUMBER: VL70-000139

DIMENSIONS:	FULL SCALE	MODEL SCALE
TOTAL DATA		
Area (Theo) - Ft ²		
Planform	425.92	0.0426
Span (Theo) - In.	315.72	3.157
Aspect Ratio	1.675	1.675
Rate of Taper	0.507	0.507
Taper Ratio	0.404	0.404
Sweep-Back Angles, Degrees.		
Leading Edge	45.000	45.000
Trailing Edge	26.249	26.249
0.25 Element Line	41.130	41.130
Chords:		
Root (Theo) WP	268.50	2.685
Tip (Theo) WP	108.47	1.085
MAC	199.81	1.998
Fus. Sta. of .25 MAC	1463.50	14.635
W.P. of .25 MAC	635.522	6.355
B.L. of .25 MAC	0.00	0.00
Airfoil Section		
Leading Wedge Angle - Deg.	10.000	10.000
Trailing Wedge Angle - Deg.	14.920	14.920
Leading Edge Radius	2.0	2.0
Void Area	13.17	0.1317
Blanketed Area	0.00	0.00

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: WING-W 127

GENERAL DESCRIPTION: Configuration 3 per Rockwell Lines VI-70-000139B

NOTE: Same as W_{loc} , except cuff, airfoil and incidence angle.

MODEL SCALE: 0.010

TEST NO.

DWG. NO. VL70-0001.39B

DIMENSIONS:

FULL-SCALE

MODEL SCALE

TOTAL DATA			
Area (Theo.)	Ft ²		
Planform		2690.00	2.269
Span (Theo) In.		935.68	9.357
Aspect Ratio		2.264	2.265
Rate of Taper		1.177	1.177
Taper Ratio		0.892	0.892
Dihedral Angle, degrees		3.500	3.500
Incidence Angle, degrees		0.500	0.500
Aerodynamic Twist, degrees		+ 3.000	+ 3.000
Sweep Back Angles, degrees			
Leading Edge		45.000	45.000
Trailing Edge		- 10.000	- 10.000
0.25 Element Line		35.000	35.000
Chords:			
Root (Theo) B.P.O.O.		639.24	6.392
Tip, (Theo) B.P.		137.50	1.375
MAC		474.50	4.745
Fus. Sta. of .25 MAC		11.000	11.000
W.P. of .25 MAC		0.000	0.000
B.L. of .25 MAC		12.000	1.200
EXPOSED DATA			
Area (Theo) Ft ²		1752.89	9.1752
Span, (Theo) In. BP108		730.00	7.307
Aspect Ratio		2.264	2.265
Taper Ratio		0.891	0.891
Chords			
Root BP108		560.40	5.604
Tip 1.00 $\frac{b}{2}$		137.50	1.375
MAC		393.00	3.930
Fus. Sta. of .25 MAC		11.000	11.000
W.P. of .25 MAC		0.000	0.000
B.L. of .25 MAC		12.000	1.200
Airfoil Section (Sackwell Mod NASA)			
XXXX-64			
Root $\frac{b}{2}$		0.10	0.10
Tip $\frac{b}{2}$		0.10	0.10
ta for (1) or (2) Sides			
Leading Edge Cuff?			
Trailing Edge Cuff?			
Wing Span 1.000000 Bus M. L. @ Sta			
Wing Span 1.000000 Interpolate Wind 0 Sta			

TABLE III.- MODEL DIMENSIONAL DATA- Continued.

MODEL COMPONENT: EXTERNAL TANK - T₂₀

GENERAL DESCRIPTION: External Oxygen Hydrogen Tank

MODEL SCALE: 0.010

DRAWING NUMBER: VL78-000062, VL72-000131

DIMENSIONS:	<u>FULL SCALE</u>	<u>MODEL SCALE</u>
Length (In.) (Nose @ X ₀ = 328.92)	<u>1846.905</u>	<u>18.469</u>
Max. Width - Dia - In. (@ X ₀ = 975.675)	<u>333.2</u>	<u>3.332</u>
Major Dia - In.	<u>330.2</u>	<u>3.302</u>
Max. Depth:		
Fineness Ratio	<u>5.65713</u>	<u>5.6571</u>
Area - Ft ²		
Max. Cross-sectional @ X ₀ =^75.675	<u>605.534</u>	<u>0.0605</u>
Major cross-sectional	<u>594.679</u>	<u>0.0595</u>
Base (based on 330.2 dia)	<u>594.679</u>	<u>0.0595</u>
WP of Tank Centerline (Z) - In.	<u>400.0</u>	<u>4.00</u>

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: ATTACH STRUCTURE - AT₁₆GENERAL DESCRIPTION: Forward orbiter/ET Attach Structure (2 member
Structure)

MODEL SCALE: 0.010

DRAWING NO.: VL78-000062B, SK-H-4011

MODEL DRAWING: SS-A00117

DIMENSIONS:	<u>MEMBER</u>	<u>FULL SCALE</u>	<u>MODEL SCALE</u>
	#1	X _O 394.38	3.944
		Y _O 0	0
		Z _O LWR ML	LWR ML
		X _T 1131.0	11.310
		Y _T 46.8	0.468
		Z _T 561.298	5.613
	#2	X _O 394.38	3.944
		Y _O 0	0
		Z _O LWR ML	LWR ML
		X _T 1131.0	11.310
		Y _T - 46.8	- 0.468
		Z _T 561.298	5.613

Diameter of Members: 5.70 IN. DIA., F.S.

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: ATTACH STRUCTURE - AT₁₇

GENERAL DESCRIPTION: Left rear orbiter/ET attach structure (2 member structure)

MODEL SCALE: 0.010

DRAWING NO.: VL78-000062B, SK-H-4013.

MODEL DRAWING: SS-A00117

DIMENSIONS:		<u>MEMBER</u>	<u>FULL SCALE</u>	<u>MOLEI SCALE</u>
#	#1	x_o	1317	13.17
		y_o	- 96.5	- 0.965
		z_o	267.5	2.675
		x_T	2058.0	20.58
		y_T	- 125.827	1.258
		z_T	515.5	5.155
	#2	x_o	1317.0	13.17
		y_o	- 96.5	- 0.965
		z_o	267.5	2.675
		x_T	2058.0	20.58
		y_T	- 125.827	1.258
		z_T	515.5	5.155

Diameter of Members: #1 11.5 In. Dia. F.S.

#2 15.5 In. Dia. F.S.

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: ATTACH STRUCTURE - AT₁₈

GENERAL DESCRIPTION: Right rear orbiter/ET attach structure (3 member structure)

MODEL SCALE: 0.010

DRAWING NO.: VL78-000062B, SK-II-4013

MODEL DRAWING: SS-A00117

DIMENSIONS:	MEMBER	FULL SCALE	MODEL SCALE
	#1	X _O 1317.00 Y _O + 96.5 Z _O 267.5 X _T 1872.0 Y _T + 125.827 Z _T 515.5	13.170 + 0.965 2.675 18.720 + 1.258 5.155
	#2	X _O 1317.0 Y _O + 96.5 Z _O 267.5 X _T 2058.0 Y _T + 125.827 Z _T 515.5	13.170 + 0.965 2.675 20.580 + 1.258 5.155
	#3	X _O 1317.0 Y _O 54.40 Z _O 19.30 X _T 2058.0 Y _T 2.5 Z _T 567.6	13.170 0.544 0.193 20.580 0.025 5.676
Diameter of Members: (in.)	#1	15.5	0.155
	#2	11.5	0.115
	#3	4.5	0.045

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: ATTACH STRUCTURE - AT₁₉

GENERAL DESCRIPTION: Forward SRB/ET attach structure (2 attach structures - Left and Right).

MODEL SCALE: 0.010

DRAWING NO.: VL78-000062B, VL72-000140, VL72-000115 MODEL DRAWING: SS-A00117

DIMENSIONS:	FRONTAL VIEW	<u>MEMBER - LEFT</u>	<u>FULL SCALE</u>	<u>MODEL SCALE</u>
		X _B		

X _B		
Y _B		
Z _B		
X _T	975.675	9.757
Y _T	166.67	+ 1.667
Z _T	+566.5	+ 5.665

MEMBER - RIGHT

X _B		
Y _B		
Z _B		
X _T	975.675	9.757
Y _T	166.67	1.667
Z _T	- 233.5	- 2.335

TABLE I.IJ. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: ATTACH STRUCTURE- AT₂₀

GENERAL DESCRIPTION: Art SRB/ET attach structure (3 member structure)

MODEL SCALE: 0.010

DRAWING NO.: VL78-000062B, VL72-000140, VL72-000115 MODEL DWG: SS-A00117

<u>DIMENSIONS:</u>	<u>MEMBER</u>	<u>FULL SCALE</u>	<u>MODEL SCALE</u>	
	#1	X _B Y _B Z _B Z _T	1317.0 ± 57.0 457.0	13.17 0.570 4.570
	#2	X _B X _T	1317.0 2058.0	13.17 20.580
	#3	X _B Y _B X _T Z _T	1317.0 ± 57.0 2058.0 343.0	13.170 ± 0.570 20.580 3.430
Diameter of Members: -(In.)		6.0	0.060	

TABLE III. - MODEL DIMENSIONAL DATA - Concluded.

MODEL COMPONENT: ATTACH STRUCTURE - AT₂₄

GENERAL DESCRIPTION: Forward orbiter/ET attach structure (2 member structure) simulating the attach structure after ET separation.

MODEL SCALE: 0.010

DRAWING NUMBER: VL78-000062B

MODEL DRAWING: SS-A00117

DIMENSIONS:	<u>MEMBER</u>	<u>FULL SCALE</u>	<u>MODEL SCALE</u>
#1	X _O	346.00	3.460
	Y _O	0	0
	Z _O	280.07	2.800
	X _T	1131.00	11.310
	Y _T	46.0	0.460
	Z _T	565.07	5.650
#2	X _O	346.00	3.460
	Y _O	0	0
	Z _O	280.07	2.800
	X _T	1131.00	11.310
	Y _T	- 46.00	- 0.460
	Z _T	280.07	2.800
Diameters of Members: (In.)		5.70	0.057

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: FEEDLINE - FL₅

GENERAL DESCRIPTION: LOX Feed line simulated between ET and Orbiter.

MODEL SCALE: 0.010

DRAWING NO.: VL78-000062E,

MODEL DRAWING: SS-A00117

DIMENSIONS:

		<u>FULL SCALE</u>	<u>MODEL SCALE</u>
Leading edge at:	X _T	1033.3	10.333
	Y _T	70.0	0.700
	X _T	1033.3	10.333
	Y _T	- 70.0	- 0.700
Trailing edge at:	X _T	2071.50	20.715
	Y _T	70.00	0.700
	Dia. - Inches.	18.80	0.188
	X _T	2071.50	20.715
	Y _T	+ 70.00	+ 0.700

Centerline of LOX Feedline located radially at $\phi = 23^{\circ}24'$

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: PRESSURE LINE - FLG

GENERAL DESCRIPTION: Max. cross-sectional area simulating LH₂ pressure line and electrical conduit box between ET and Orbiter.

MODEL SCALE: 0.010

DRAWING NO.: VL78-000062B

MODEL DRAWING NO.: SS-A00117

DIMENSIONS:	<u>FULL SCALE</u>	<u>MODEL SCALE</u>
Leading edge at: X _T	1127.1	11.271
Y _T	110.3	1.103
Trailing edge at: X _T	2062.1	20.621
Y _T	110.3	1.103

Centerline of LH₂ pressure line located radially at $\phi = 33^{\circ}45'$

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT : LH₂ UMBILICAL FEEDLINE - FL₂

GENERAL DESCRIPTION : LH₂ Umbilical Feedline with an electrical quick
disconnect box between the Orbiter and ET.

MODEL SCALE: 0.010

DRAWING NUMBER VL78-000062B

DIMENSIONS	FULL SCALE	MODEL SCALE
Centerline at X _T	<u>2071.5</u>	<u>20.715</u>
Max Width	<u>32.2</u>	<u>0.312</u>
Max Depth	<u>37.5</u>	<u>0.375</u>
Diameter	<u>17.0</u>	<u>0.170</u>
Area		
Max. Cross-Sectional		
Planform		
Wetted		
Base		

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: FAIRING - FR₆

DESCRIPTION: Cross member between aft ET/orbiter attach structures

MODEL SCALE: 0.010

DRAWING NO.: VL78-000062B, VL78-000050 MODEL DRAWING: SS-A00117

DIMENSIONS:	<u>FULL SCALE</u>	<u>MODEL SCALE</u>
Leading edge at X _T	2035.50	20.355
Length	15.00	0.150
Width	193.0	1.930

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: ET PROTUBERANCE - PT₁₂

GENERAL DESCRIPTION: Lightning rod attached to ET nose.

MODEL SCALE: 0.010

DRAWING NO.: VL78-000068B

DIMENSIONS:	<u>FULL SCALE</u>	<u>MODEL SCALE</u>
Length	30.90	0.309
Diameter - In.	3.20	0.032

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: ET PROTUBERANCE - PT₁₃

GENERAL DESCRIPTION: Maximum cross-sectional area simulating LOX recirculation line and electrical conduit box on planform view of external tank, T₂₀.

MODEL SCALE: 0.010

DRAWING NO.: VL78-000062B

MODEL DRAWING: SS-A00117

DIMENSIONS:

		<u>FULL SCALE</u>	<u>MODEL SCALE</u>
Leading edge at:	X _T	1208.3	12.083
	Y _T	+ 95.0	+ 0.950
	X _T	1208.3	12.083
	Y _T	- 95.0	- 0.950
Trailing edge at:	X _T	2060.5	20.605
	Y _T	+ 95.0	+ 0.950
	X _T	2060.5	20.605
	Y _T	- 95.0	- 0.950

Centerline of LOX recirculation line located radially at $\phi = 33^{\circ}45'$.

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: ET PROTUBERANCE - PT₁₄

GENERAL DESCRIPTION: LOX pressure line on Tank T₂₀

MODEL SCALE: 0.010

DRAWING NO.: VL78-000062B

MODEL DRAWING:

DIMENSIONS:

		<u>FULL SCALE</u>	<u>MODEL SCALE</u>
Leading edge at:	X _T	355.90	3.559
	Y _T	6.0	0.06
Trailing edge at:	X _T	2060.5	20.605
	Y _T	+ 87.0	+ 0.870

Centerline of LOX pressure line located radially at $\phi = 23^{\circ}24'$.

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT: SRB SEPARATION PUSH-OFF PAD - PT₁₉

GENERAL DESCRIPTION: Forward ET/SRB Separation pads (push-off pads)

MODEL SCALE: 0.010

DRAWING NO.: VL78-000062B

MODEL DRAWING: SS-A00117

DIMENSIONS:	MEMBER		<u>FULL SCALE</u>	<u>MODEL SCALE</u>
#1	X _T		450.0	4.50
	Y _T		975.60	9.756
	Z _T		166.50	1.665
#2	X _T		450.00	4.500
	Y _T		- 975.60	9.756
	Z _T		166.50	1.665

TABLE III. - MODEL DIMENSIONAL DATA - Continued.

MODEL COMPONENT NOSE CONE LINES - PT₂₀
 GENERAL DESCRIPTION Maximum cross-sectional area simulating the
LOX pressure line and electrical conduit on top of external tank
(T₂₀) nose cone area.
 MODEL SCALE: 0.010
 DRAWING NUMBER VL78-000062B

DIMENSIONS	FULL SCALE	MODEL SCALE
Leading Edge at: X _T	<u>360.92</u>	<u>3.609</u>
Y _T	<u>34.0</u>	<u>0.340</u>
Trailing Edge at: X _T	<u>955.1</u>	<u>9.551</u>
Y _T	<u>336.5</u>	<u>3.365</u>
Area	_____	_____
Max. Cross-Sectional	_____	_____
Planform	_____	_____
Wetted	_____	_____
Base	_____	_____
Centerline of lines located radially at $\phi = 33^{\circ}45'$		

Notes

- Positive directions of force coefficients, moment coefficients, and angles are indicated by arrows
- For clarity, origins of wind and stability axes have been displaced from the center of gravity






Figure 1. - Axis Systems.




ORIGINAL PAGE IS
OF POOR QUALITY

a. Integrated Configuration 0₉ T₂₀
 Figure 2. - Model sketches.




b. Orbiter - O₉


Figure 2. - Continued.



c. External Tank (T20) per R. I. Drawing VL78-000062B
Figure 2. - Continued.



- NOTES:**
- 1) PRESSURE TUBES 1 & 2 ARE MATED TO EACH OTHER
 - 2) PRESSURE TUBES 3 & 4 ARE MATED TO EACH OTHER
 - 3) PRESSURE TUBES 7, 8 & 9 ARE MATED TO EACH OTHER



d. Base Pressure Orifice Locations
Figure 2. - Concluded.

ORIGINAL PAGE IS
ONE SIDE OF SHEET

Figure 3. - Model installation photographs.



a. Orbiter and Tank, Side View


Figure 3. - Continued.


b. Orbiter and Tank, 3/4 Rear View



c. Tank Only, Rolled 90° for Sideslip Run, 3/4 Rear View from Right Side

Figure 3. - Continued.






2. Tarz Stry, acclined 90° for Sideslip Run, Left Side View (Top of Model is Toward Viewer)
Figure 3. - Concluded.

DATA FIGURES

DATA SET NUMBER:
12 SEC 1 2 3A18 - ARC 3.5 191 - ORBITER + TANK
3A A-10 - ALPHA, DEG.

REFERENCE INFORMATION
S.P.F. 2680.0000 SQ.FT.
S.P.F. 1390.2000 N.Y.
S.P.F. 120.2000 N.Y.
Y.W.P. 979.0000 N.Y.
Y.W.P. 400.0000 N.Y.
SCALE



GROUT BODY AXIAL FORCE COEFFICIENT, CAF

FIG. 4 EFFECT OF MACH NUMBER ON SECOND STAGE LONGITUDINAL AERODYNAMIC CHAR.

MACH - 5.29

PAGE 1

2.33

2.32. 4. SEEDS 25 MCG - 100% SEEDS 25. SEEDS 25%.

2.33. 2.34.

2.34. ANGLE OF A-AXIS, A-PHA. 25 DEGREES
2.35. 25 25 25

2.36. 2.37. 2.38.

2.39. 2.40. 2.41.

2.42. 2.43. 2.44.

2.45. 2.46. 2.47.

2.48. 2.49. 2.50.

2.51. 2.52. 2.53.

2.54. 2.55. 2.56.

2.57. 2.58. 2.59.

2.60. 2.61. 2.62.

2.63. 2.64. 2.65.

2.66. 2.67. 2.68.

2.69. 2.70. 2.71.

2.72. 2.73. 2.74.

2.75. 2.76. 2.77.

2.78. 2.79. 2.80.

2.81. 2.82. 2.83.

1. ORIGAMI AXIAL 1.913. C011110111. CAI



DATA SET: SYMBOL: DESCRIPTION: DATA 3.519 - C391ER + MACH 3.5 ALPHASE

DATA SET: SYMBOL: DESCRIPTION: DATA 3.519 - C391ER + MACH 3.5 ALPHASE

REFERENCE INFORMATION:
SCALE 2600.0000 SQ.FT.
RATE 280.3000
BREEZE 150.3000
WIND 150.3000
WIND 200.0000
WIND 400.0000
SCALE 200.0000




FIG. 4 EFFECT OF MACH NUMBER ON SECOND STAGE LONGITUDINAL AERODYNAMIC CHAR.


MACH = 1.029

FIG. 4 EFFECT OF MACH NUMBER ON SECOND STAGE LONGITUDINAL AERODYNAMIC CHAR.

BASE 3

DATA SET NUMBER: 225
TEST NUMBER: 218 - ARC 3.519: - CRATER + TAN
DATA STAGE: 2ND STAGE

CONFIGURATION DESCRIPTION:
REFERENCE INFORMATION:
SREF: 2690.0000 S.C.F.
REF: 1260.3000
BREF: 1260.3000
XREF: 59.0000 X.T.
YREF: 400.0000 Y.T.
SCALE: .0000




NORMAL AEROCOEFFICIENT, CN

FIG. 4. EFFECT OF MACH NUMBER ON SECOND STAGE LONGITUDINAL AERODYNAMIC CHAR.
MACH = 5.29

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 1 & 2 SEC: (O) 1A18 - ARC 3.5 19 - CRADLER + TANK
 3 & 4 SEC: (C) 1A18 - ARC 3.5 19 - CRADLER + TANK

BETA .000 RUDDER .000 ELEVON .000
 .000 .000 .000
 .000 .000 .000

REFERENCE INFORMATION
 SREF 2680.0000 SC.FT.
 RREF 1280.3000 IN.
 BREF 1280.3000 IN.
 XRPD 9.9 .0000 X²
 YRPD 400 .0000 Y²
 ZRPD 200 .0000 Z²
 SCALE .0100



NORMAL FORCE COEFFICIENT, CN


FIG. 4 EFFECT OF MACH NUMBER ON SECOND STAGE LONGITUDINAL AERODYNAMIC CHAR.

$C_D \text{MACH} = 7.32$

DATA SET SWAC-
(* SEC 1) C CONFIGURATION DESCRIPTION:
(* SEC 2) DATA NOT AVAILABLE

BETA ROLL ELEVON
.000 .000 .000
.000 .000 .000
REFERENCE INFORMATION
SREF 2680.0000 SC.FT.
LREF 1280.3000 IN.
BREF 676.3000 IN.
WDP 2680.0000 IN.YT
WDP 400.0000 IN.YT
SCALE .0100 SIC.


NORMAL FOR COEFFICIENT, CN



E13.4 EFFECT OF MACH NUMBER ON SECOND STAGE LONGITUDINAL AERODYNAMIC CHAR.
MACH = 10.29

DATA SEC. 1: # SEC. 1: 1: # SEC. 2: 2:
 DATA SEC. 1: DATA SEC. 2: DATA SEC. 3:
 CONFIGURATION DESCRIPTION: DATA SEC. 1 - ARC 3.5 19: - CARRIER + TANK

PITCHING MOMENT COEFFICIENT, CLM
 REFERENCE INFORMATION
 SREF 2690.0000 SQ.FT.
 BREF 1280.3000 N.
 BREF 1280.3000 N.
 YWRF 979.0000 N.Y.
 YWRF 979.0000 N.Y.
 ZWRF 400.0000 N.Z
 SCALE .010




PITCHING MOMENT COEFFICIENT, CLM

FIG. 4 EFFECT OF MACH NUMBER ON SECOND STAGE LONGITUDINAL AERODYNAMIC CHAR.

$C_{L/MAC} = 5.29$

DATA SETS - CONFIGURATION DESCRIPTION
 1: SEC 1: MACH 3.5 - ARC 3.5 - SPINTER + TAN.
 2: SEC 1: MACH 3.5 - ARC 3.5 - SPINTER + TAN.



PITCHING MOMENT COEFFICIENT, CLM

FIG. 4 EFFECT OF MACH NUMBER ON SECOND STAGE LONGITUDINAL AERODYNAMIC CHAR.

$C_{L,MACH} = ? .32$

PAGE 8

DATA SET NUMBER: 12 SEC 1
 12 SEC 2
 12 SEC 3
 DATA 18 - ARC 3.5 '91 - CRATER + TANK
 DATA NO. AATL-3E

REFERENCE INFORMATION
 SREF 2650.0000 SQ.FT.
 SREF 1250.3000 IN.
 SREF 1250.3000 IN.
 XREF 9.9. X1
 YREF 400.0000 IN. Z1
 ZREF 400.0000 SC-E

PITCHING MOMENT COEFFICIENT, CLM





FIG. 4 EFFECT OF MACH NUMBER ON SECOND STAGE LONGITUDINAL AERODYNAMIC CHAR.

(C_L)(MACH) = 10.29

PAGE 9

DATA SET NUMBER: 2 CONFIGURATION DESCRIPTION: DATA SET NUMBER: 1A: B - ARC 3.5 19: - CRATER + TANK

REFERENCE INFORMATION
SREF 2890.0000 SC.FT.
SREF 1250.3000 X
SREF 99.0000 Y
XW2 1260.0000 XT
YW2 400.0000 YT
SCALE .25




NOMINAL + DRIFT COEFFICIENT, CLM

FIG. 4 EFFECT OF MACH NUMBER ON SECOND STAGE LONGITUDINAL AERODYNAMIC CHAR.
C_M(MACH) = 5.29

DATA SET 5 Stage
1:2 SEC'S : 1
2:2 SEC'S : 1

CONFIGURATION DESCRIPTION:
A1B = ARC 3.5 19° - SEAT TIER + TAN
A1B = ARC 3.5 19° - SEAT TIER + TAN

REFERENCE INFORMATION
SREF 2620.0000 50 FT.
SREF 1260.3000
SREF 89.0000 X
XMP 400.0000 Y
ZMP .0000 Z
SCAL.




NORMAL FORCE COEFFICIENT. CN

FIG. 4 EFFECT OF MACH NUMBER ON SECOND STAGE LONGITUDINAL AERODYNAMIC CHAR.

DATA SET SYMBOL: CONFIGURATION DESCRIPTION:
1218 - ARC 3.5 19: - C93:1ER + TANK
DATA IS AVAILABLE

REFERENCE INFORMATION
SREF 2680.0000 SC.FT.
REF 1250.0000 IN.
REF 1250.0000 IN.
YREF 579.0000 IN.YT
XREF 111.0000 IN.XT
ZREF 400.0000 IN.ZT
SCALE .25



NOMINAL + GRCL COEFFICIENT, CN

FIG. 4 EFFECT OF MACH NUMBER ON SECOND STAGE LONGITUDINAL AERODYNAMIC CHORD
CONVENTION = 12.28
PAGE .2

FIG. 8 - ARC 3.5 19 - TAN

SPEC. MACH. 5.000 35°, ELEV. .000
C 4.320 .000 2000 .000
O 3.000

REFERENCE INFORMATION.
SPEED, MPH. 2680, 3000
SPEED, FT./SEC. 1950, 2325
ELEV. 35°
ANGLE OF ATTACK, DEGREES 20, 30
SCALE 4000, 5000




FIG. 8 - FLAT PLATE AIRFOIL ISOLATED LONGITUDINAL AERODYNAMIC CHAR.

-50 -40 -30 -20 -10 0 20 30
ANGLE OF ATTACK, ALPHA, DEGREES

FIG. 5 EFFECT OF MACH NUMBER ON ISOLATED ET LONGITUDINAL AERODYNAMIC CHAR.


1A:8 - ARC 3.5 :90 - TAN

CROSS:

WING
5.282
.300
10.386

PARAMETRIC VALUES
BETA .000
E.E.00 .000

REFERENCE FREQUENCIES
SPL 2600 2800 3000
3000 3200 3400
3200 3400 3600
3400 3600 3800
3600 3800 4000
3800 4000 4200
4000 4200 4400



NORMA L DRA F 00411011 N. CN

-13.5 EFFECT OF WING NUMBER ON SEPARATED LENGTH SPECTRUM FREQUENCY SPECTRUM

DATE 14

MACH = ARC 3.5 19: TANK

SPEC.
MACH .5-.999
ANGLE OF ATTACK .300
ELEV. ANG. .000
ROLL ANG. .000
RUDER .000
FLAP .000
AUXILIARY FLAPS .000

(RE. 5006)

PITCHING MOMENT COEFFICIENT. CLM





FIG. 5 EFFECT OF MACH NUMBER ON ISOLATED ET LONGITUDINAL AERODYNAMIC CHAR.

PAGE 15

MACH 5.22 4RC 3.5 : 9: TAN
 5.28 3.71 P.D.
 5.32 3.80
 5.38 3.88

STAB
 MACH .300
 2000 .2000
 .300

(RES206)



NOMINAL DRAFT COEFFICIENT, CN

FIG. 5 EFFECT OF MACH NUMBER ON ISOLATED ET LONGITUDINAL AERODYNAMIC CHAR.

PAGE 16

DATA SET SYMBOL: C
 * SEC2: 1A1B - ARC 3.5 91 - CENTER : TANK
 + SEC3: 1A1B - ARC 3.5 91 - CENTER : TANK
 + SEC4: 1A1B - ARC 3.5 91 - CENTER : TANK




FIG. 6 EFFECT OF ANGLE OF ATTACK ON SECOND STAGE LATERAL-DIRECTIONAL AERO. CHAR.
CLAVING = 5.29

DATA SET SYMBOL - CONFIGURATION DESCRIPTION

12-20021	C	ARC 3.5	18°	-1.238	INTER + TAN
12-20031	C	ARC 3.5	18°	-1.238	INTER + TAN
12-20041	S	ARC 3.5	18°	-1.238	INTER + TAN

REFERENCE INFORMATION
 SPREF 2690.0000 SQ. FT.
 SPREF 1260.3000 IN.
 SPREF 1260.3000 IN.
 SPREF 1.979.0000 IN.
 YREF 1.979.0000 IN.
 XREF 400.0000 IN.
 ZREF 400.0000 IN.
 SCALE .5




FIG. 6 EFFECT OF ANGLE OF ATTACK ON SECOND STAGE LATERAL-DIRECTIONAL AERO. CHAR.

DATA = 7.32
 C2VAC =

FIG. 6 EFFECT OF ANGLE OF ATTACK ON SECOND STAGE LATERAL-DIRECTIONAL AERO. CHAR.

PAGE 18

DATA SOURCE: CONFIGURATION DESCRIPTION:
 1.2 SOC2: C1 18 - ARC 3.5 19 - CRATER + TANK
 1.2 SOC3: C1 18 - ARC 3.5 19 - CRATER + TANK
 1.2 SOC4: C1 18 - ARC 3.5 19 - CRATER + TANK
 1.2 SOC5: C1 18 - ARC 3.5 19 - CRATER + TANK

REFERENCE INFORMATION	SD.FT.
SREF	2500.0000
REF	2500.3000
REF	2500.3000
XMR	95.0000
YMR	100.0000
ZMR	400.0000
SCALE	.0100




FIG. 6 EFFECT OF ANGLE OF ATTACK ON SECOND STAGE LATERAL-DIRECTIONAL AERC. CHAR.


COEFAC = 1.C.28
PAGE : 9

PAGE : 9
FIG. 6 EFFECT OF ANGLE OF ATTACK ON SECOND STAGE LATERAL-DIRECTIONAL AERC. CHAR.

DATA SET SYMBOL
 (2) SEC2: C
 (2) SEC3: A
 (2) SEC4: D

CONFIGURATION DESCRIPTION
 1A18 - ARC 3.5 18 - SP3 TVER + TANX
 1A18 - ARC 3.5 18 - SP3 TVER + TANY
 1A18 - ARC 3.5 18 - SP3 TVER + TANZ

REFERENCE INFORMATION
 SREF 2500.000 50.FT.
 SREF 2500.300 100.
 SREF 2500.300 100.
 XREF 9.0 .000 100.
 YREF 400 .000 100.
 ZREF .000 100.



YAWING MOMENT COEFFICIENT, CYN (BODY AXIS)

FIG. 6 EFFECT OF ANGLE OF ATTACK ON SECOND STAGE LATERAL-DIRECTIONAL AERO. CHAR.
 C α MAX = 5.29


PAGE 23

CONF. S : SYMBC
 14 SC01 : 0
 14 SC02 : 1
 14 SC03 : 0
 14 SC04 : 0

CONFIGURATION DESCRIPTION
 1418 - ARC 3-5 191 - CRB1 TIER 1 TANK
 1418 - ARC 3-5 191 - CRB3 TIER 2 TANK
 1418 - ARC 3-5 191 - CRB3 TIER 3 TANK

ALPHA RUDER ELEVON
 4.000 .000 .000
 .000 .000 .000
 -.000 .000 .000

REFERENCE INFORMATION
 REF 2800.0000 SQ.FT.
 P1 1360.3000
 P2 1360.3000
 Y2 519.0000 X2 27
 YRP 450.0000 ZRP .0000
 SCALE .0100




YAWING MOMENT COEFFICIENT, CYN (BODY AXIS)

FIG. 6 EFFECT OF ANGLE OF ATTACK ON SECOND STAGE LATERAL-DIRECTIONAL AERO. CHAR.
 (3) MAC = 7.32

DATA SET: S1-80
 1.2 SEC2: 0118 - ARC 3.5 191 - CR311TER : TANK
 1.2 SEC3: 0118 - ARC 3.5 191 - CR311TER : TANK
 1.2 SEC4: 0118 - ARC 3.5 191 - CR311TER : TANK

REFERENCE INFORMATION
 A-PHI R-JDDER E-ELEVN
 4.000 .000 .000
 .000 .000 .000
 -4.000 .000 .000
 SEEF 2690.0000 SO.F1.
 BREF 1260.3000 N.
 BREF 1260.3000 N.
 YWRD 979.0000 X.
 YWRD 400.0000 N.
 SCALE .5.00 21



YAWING MOM IN COORDINATE SYSTEM (BODY AXIS)

FIG. 6 EFFECT OF ANGLE OF ATTACK ON SECOND STAGE LATERAL-DIRECTIONAL AERO. CHAR.

COVAC = 10.28

PAGE 22

DATA SET SYMBOL

1	SET 2
2	SET 3
3	SET 4

CONFIGURATION DESCRIPTION

1A1B	AFC 3.5	1B - CENTER TANK
1A1B	AFC 3.5	1B - CENTER TANK
1A1B	AFC 3.5	1B - CENTER TANK

REFERENCE INFORMATION

SREF	2890.0000
XREF	1.903300
YREF	.1293300
ZREF	.993300
XRP	.993300
YRP	.003300
ZRP	.003300

SCA.E

ROLLING MOMENT COEFFICIENT, C_{B1} (BODY AXIS)




FIG. 6 EFFECT OF ANGLE OF ATTACK ON SECOND STAGE LATERAL-DIRECTIONAL AERO. CHAR.

C_{B1}(AFC) = 5.29

PAGE 23

DATA SET NUMBER: CONFIGURATION DESCRIPTION:
 1: SEC1: A18 - ARC 3.5 deg - CRAB TTER + TAN
 2: SEC2: A18 - ARC 3.5 deg - CRAB TTER - TAN
 3: SEC3: A18 - ARC 3.5 deg - CRAB TTER - TAN

	ALPHA	RUDER	ELEVON
SEC1	.000	.000	.000
SEC2	.000	.000	.000
SEC3	-.000	.000	.000

SCALE





FIG. 6 EFFECT OF ANGLE OF ATTACK ON SECOND STAGE LATERAL-DIRECTIONAL AERO. CHAR.
 (3:MAC = 0.32)

ALPHA	RUDDER	ELEVON	REFERENCE INFORMATION		
			SREF	2690	2000
4.000	.000	.000	-REF	-2900	-3000
.000	.000	.000	-REF	-2900	-3000
-4.000	.000	.000	-REF	-2900	-3000

卷之二



ROLLING MOMENT COEFFICIENT, C_{RL} (BODY AXES)

FIG. 6. EFFECT OF ANGLE OF ATTACK ON SECOND STAGE LATERAL-DIRECTIONAL AERO.
CHAR.

DATA SET: S₁ SEC.
 1.2 SEC1: 0
 1.2 SEC2: 0
 1.2 SEC3: 0
 1.2 SEC4: 0

CONFIGURATION DESCRIPTION
 TAIB - ARC 3.5 19 - ORBITER + TANK
 TAIB - ARC 3.5 19 - 233:ITER + TANK
 TAIB - ARC 3.5 19 - 233:ITER + TANK

REFERENCE INFORMATION	SCA. FT.
SPD	7680.0000
SPD	1420.3200
WWD	619.2606
WWD	455.0000
INR2	455.0000
SCALE	





FIG. 5 EFFECT OF ANGLE OF ATTACK ON SECOND STAGE LATERAL-DIRECTIONAL AEROC. CAR.

DATA SET: S₂ SEC.
 1.2 SEC1: 0
 1.2 SEC2: 0
 1.2 SEC3: 0
 1.2 SEC4: 0

FIG. 6 VARYING MEMENT COEFFICIENT, CYN (BODY AX:S)
 DATA SET: S₂ SEC.
 1.2 SEC1: 0
 1.2 SEC2: 0
 1.2 SEC3: 0
 1.2 SEC4: 0

DATA SET: SIMC
 # SEC 2: 14.8 - ARC 3.5 19° - C2B1TER : TAN
 # SEC 3: 14.8 - ARC 3.5 19° - C2B1TER : TAN
 # SEC 4: 14.8 - ARC 3.5 19° - C2B1TER : TAN
 REFERENCE INFORMATION
 SPEC 2620, 10000
 SREF 1500, 3000
 3255 1500, 3000
 XMAS 575, 1000
 YMAS 400, 800
 ZMAS 100, 200
 SCALE .000




SLOP + ORIG COEFFICIENT, C_x

FIG. 7.6.6 EFFECT OF ANGLE OF ATTACK ON SECOND STAGE LATERAL-DIRECTIONAL AERO. CHAR.
 (3) $\Delta MAC = 7.37$
 DATE 27

DATE 28

TESTS OF VARIOUS STAGES IN SECOND STAGE - AT 2000' ELEVATION - TIDE, 0.00

Y = 1.12 + .12 X COEFFICIENT, CVN (BED) AXES: 1.12, 1.13



ADDITIONAL NOTES

1. SE 1 STAGE
2. SE 2
3. SE 3
4. SE 4
5. SE 5
6. SE 6
7. SE 7
8. SE 8
9. SE 9
10. SE 10
11. SE 11
12. SE 12
13. SE 13
14. SE 14
15. SE 15
16. SE 16
17. SE 17
18. SE 18
19. SE 19
20. SE 20
21. SE 21
22. SE 22
23. SE 23
24. SE 24
25. SE 25
26. SE 26
27. SE 27
28. SE 28
29. SE 29
30. SE 30
31. SE 31
32. SE 32
33. SE 33
34. SE 34
35. SE 35
36. SE 36
37. SE 37
38. SE 38
39. SE 39
40. SE 40
41. SE 41
42. SE 42
43. SE 43
44. SE 44
45. SE 45
46. SE 46
47. SE 47
48. SE 48
49. SE 49
50. SE 50
51. SE 51
52. SE 52
53. SE 53
54. SE 54
55. SE 55
56. SE 56
57. SE 57
58. SE 58
59. SE 59
60. SE 60
61. SE 61
62. SE 62
63. SE 63
64. SE 64
65. SE 65
66. SE 66
67. SE 67
68. SE 68
69. SE 69
70. SE 70
71. SE 71
72. SE 72
73. SE 73
74. SE 74
75. SE 75
76. SE 76
77. SE 77
78. SE 78
79. SE 79
80. SE 80
81. SE 81
82. SE 82
83. SE 83
84. SE 84
85. SE 85
86. SE 86
87. SE 87
88. SE 88
89. SE 89
90. SE 90
91. SE 91
92. SE 92
93. SE 93
94. SE 94
95. SE 95
96. SE 96
97. SE 97
98. SE 98
99. SE 99
100. SE 100
101. SE 101
102. SE 102
103. SE 103
104. SE 104
105. SE 105
106. SE 106
107. SE 107
108. SE 108
109. SE 109
110. SE 110
111. SE 111
112. SE 112
113. SE 113
114. SE 114
115. SE 115
116. SE 116
117. SE 117
118. SE 118
119. SE 119
120. SE 120
121. SE 121
122. SE 122
123. SE 123
124. SE 124
125. SE 125
126. SE 126
127. SE 127
128. SE 128
129. SE 129
130. SE 130
131. SE 131
132. SE 132
133. SE 133
134. SE 134
135. SE 135
136. SE 136
137. SE 137
138. SE 138
139. SE 139
140. SE 140
141. SE 141
142. SE 142
143. SE 143
144. SE 144
145. SE 145
146. SE 146
147. SE 147
148. SE 148
149. SE 149
150. SE 150
151. SE 151
152. SE 152
153. SE 153
154. SE 154
155. SE 155
156. SE 156
157. SE 157
158. SE 158
159. SE 159
160. SE 160
161. SE 161
162. SE 162
163. SE 163
164. SE 164
165. SE 165
166. SE 166
167. SE 167
168. SE 168
169. SE 169
170. SE 170
171. SE 171
172. SE 172
173. SE 173
174. SE 174
175. SE 175
176. SE 176
177. SE 177
178. SE 178
179. SE 179
180. SE 180
181. SE 181
182. SE 182
183. SE 183
184. SE 184
185. SE 185
186. SE 186
187. SE 187
188. SE 188
189. SE 189
190. SE 190
191. SE 191
192. SE 192
193. SE 193
194. SE 194
195. SE 195
196. SE 196
197. SE 197
198. SE 198
199. SE 199
200. SE 200
201. SE 201
202. SE 202
203. SE 203
204. SE 204
205. SE 205
206. SE 206
207. SE 207
208. SE 208
209. SE 209
210. SE 210
211. SE 211
212. SE 212
213. SE 213
214. SE 214
215. SE 215
216. SE 216
217. SE 217
218. SE 218
219. SE 219
220. SE 220
221. SE 221
222. SE 222
223. SE 223
224. SE 224
225. SE 225
226. SE 226
227. SE 227
228. SE 228
229. SE 229
230. SE 230
231. SE 231
232. SE 232
233. SE 233
234. SE 234
235. SE 235
236. SE 236
237. SE 237
238. SE 238
239. SE 239
240. SE 240
241. SE 241
242. SE 242
243. SE 243
244. SE 244
245. SE 245
246. SE 246
247. SE 247
248. SE 248
249. SE 249
250. SE 250
251. SE 251
252. SE 252
253. SE 253
254. SE 254
255. SE 255
256. SE 256
257. SE 257
258. SE 258
259. SE 259
260. SE 260
261. SE 261
262. SE 262
263. SE 263
264. SE 264
265. SE 265
266. SE 266
267. SE 267
268. SE 268
269. SE 269
270. SE 270
271. SE 271
272. SE 272
273. SE 273
274. SE 274
275. SE 275
276. SE 276
277. SE 277
278. SE 278
279. SE 279
280. SE 280
281. SE 281
282. SE 282
283. SE 283
284. SE 284
285. SE 285
286. SE 286
287. SE 287
288. SE 288
289. SE 289
290. SE 290
291. SE 291
292. SE 292
293. SE 293
294. SE 294
295. SE 295
296. SE 296
297. SE 297
298. SE 298
299. SE 299
300. SE 300
301. SE 301
302. SE 302
303. SE 303
304. SE 304
305. SE 305
306. SE 306
307. SE 307
308. SE 308
309. SE 309
310. SE 310
311. SE 311
312. SE 312
313. SE 313
314. SE 314
315. SE 315
316. SE 316
317. SE 317
318. SE 318
319. SE 319
320. SE 320
321. SE 321
322. SE 322
323. SE 323
324. SE 324
325. SE 325
326. SE 326
327. SE 327
328. SE 328
329. SE 329
330. SE 330
331. SE 331
332. SE 332
333. SE 333
334. SE 334
335. SE 335
336. SE 336
337. SE 337
338. SE 338
339. SE 339
340. SE 340
341. SE 341
342. SE 342
343. SE 343
344. SE 344
345. SE 345
346. SE 346
347. SE 347
348. SE 348
349. SE 349
350. SE 350
351. SE 351
352. SE 352
353. SE 353
354. SE 354
355. SE 355
356. SE 356
357. SE 357
358. SE 358
359. SE 359
360. SE 360
361. SE 361
362. SE 362
363. SE 363
364. SE 364
365. SE 365
366. SE 366
367. SE 367
368. SE 368
369. SE 369
370. SE 370
371. SE 371
372. SE 372
373. SE 373
374. SE 374
375. SE 375
376. SE 376
377. SE 377
378. SE 378
379. SE 379
380. SE 380
381. SE 381
382. SE 382
383. SE 383
384. SE 384
385. SE 385
386. SE 386
387. SE 387
388. SE 388
389. SE 389
390. SE 390
391. SE 391
392. SE 392
393. SE 393
394. SE 394
395. SE 395
396. SE 396
397. SE 397
398. SE 398
399. SE 399
400. SE 400
401. SE 401
402. SE 402
403. SE 403
404. SE 404
405. SE 405
406. SE 406
407. SE 407
408. SE 408
409. SE 409
410. SE 410
411. SE 411
412. SE 412
413. SE 413
414. SE 414
415. SE 415
416. SE 416
417. SE 417
418. SE 418
419. SE 419
420. SE 420
421. SE 421
422. SE 422
423. SE 423
424. SE 424
425. SE 425
426. SE 426
427. SE 427
428. SE 428
429. SE 429
430. SE 430
431. SE 431
432. SE 432
433. SE 433
434. SE 434
435. SE 435
436. SE 436
437. SE 437
438. SE 438
439. SE 439
440. SE 440
441. SE 441
442. SE 442
443. SE 443
444. SE 444
445. SE 445
446. SE 446
447. SE 447
448. SE 448
449. SE 449
450. SE 450
451. SE 451
452. SE 452
453. SE 453
454. SE 454
455. SE 455
456. SE 456
457. SE 457
458. SE 458
459. SE 459
460. SE 460
461. SE 461
462. SE 462
463. SE 463
464. SE 464
465. SE 465
466. SE 466
467. SE 467
468. SE 468
469. SE 469
470. SE 470
471. SE 471
472. SE 472
473. SE 473
474. SE 474
475. SE 475
476. SE 476
477. SE 477
478. SE 478
479. SE 479
480. SE 480
481. SE 481
482. SE 482
483. SE 483
484. SE 484
485. SE 485
486. SE 486
487. SE 487
488. SE 488
489. SE 489
490. SE 490
491. SE 491
492. SE 492
493. SE 493
494. SE 494
495. SE 495
496. SE 496
497. SE 497
498. SE 498
499. SE 499
500. SE 500
501. SE 501
502. SE 502
503. SE 503
504. SE 504
505. SE 505
506. SE 506
507. SE 507
508. SE 508
509. SE 509
510. SE 510
511. SE 511
512. SE 512
513. SE 513
514. SE 514
515. SE 515
516. SE 516
517. SE 517
518. SE 518
519. SE 519
520. SE 520
521. SE 521
522. SE 522
523. SE 523
524. SE 524
525. SE 525
526. SE 526
527. SE 527
528. SE 528
529. SE 529
530. SE 530
531. SE 531
532. SE 532
533. SE 533
534. SE 534
535. SE 535
536. SE 536
537. SE 537
538. SE 538
539. SE 539
540. SE 540
541. SE 541
542. SE 542
543. SE 543
544. SE 544
545. SE 545
546. SE 546
547. SE 547
548. SE 548
549. SE 549
550. SE 550
551. SE 551
552. SE 552
553. SE 553
554. SE 554
555. SE 555
556. SE 556
557. SE 557
558. SE 558
559. SE 559
560. SE 560
561. SE 561
562. SE 562
563. SE 563
564. SE 564
565. SE 565
566. SE 566
567. SE 567
568. SE 568
569. SE 569
570. SE 570
571. SE 571
572. SE 572
573. SE 573
574. SE 574
575. SE 575
576. SE 576
577. SE 577
578. SE 578
579. SE 579
580. SE 580
581. SE 581
582. SE 582
583. SE 583
584. SE 584
585. SE 585
586. SE 586
587. SE 587
588. SE 588
589. SE 589
590. SE 590
591. SE 591
592. SE 592
593. SE 593
594. SE 594
595. SE 595
596. SE 596
597. SE 597
598. SE 598
599. SE 599
600. SE 600
601. SE 601
602. SE 602
603. SE 603
604. SE 604
605. SE 605
606. SE 606
607. SE 607
608. SE 608
609. SE 609
610. SE 610
611. SE 611
612. SE 612
613. SE 613
614. SE 614
615. SE 615
616. SE 616
617. SE 617
618. SE 618
619. SE 619
620. SE 620
621. SE 621
622. SE 622
623. SE 623
624. SE 624
625. SE 625
626. SE 626
627. SE 627
628. SE 628
629. SE 629
630. SE 630
631. SE 631
632. SE 632
633. SE 633
634. SE 634
635. SE 635
636. SE 636
637. SE 637
638. SE 638
639. SE 639
640. SE 640
641. SE 641
642. SE 642
643. SE 643
644. SE 644
645. SE 645
646. SE 646
647. SE 647
648. SE 648
649. SE 649
650. SE 650
651. SE 651
652. SE 652
653. SE 653
654. SE 654
655. SE 655
656. SE 656
657. SE 657
658. SE 658
659. SE 659
660. SE 660
661. SE 661
662. SE 662
663. SE 663
664. SE 664
665. SE 665
666. SE 666
667. SE 667
668. SE 668
669. SE 669
670. SE 670
671. SE 671
672. SE 672
673. SE 673
674. SE 674
675. SE 675
676. SE 676
677. SE 677
678. SE 678
679. SE 679
680. SE 680
681. SE 681
682. SE 682
683. SE 683
684. SE 684
685. SE 685
686. SE 686
687. SE 687
688. SE 688
689. SE 689
690. SE 690
691. SE 691
692. SE 692
693. SE 693
694. SE 694
695. SE 695
696. SE 696
697. SE 697
698. SE 698
699. SE 699
700. SE 700
701. SE 701
702. SE 702
703. SE 703
704. SE 704
705. SE 705
706. SE 706
707. SE 707
708. SE 708
709. SE 709
710. SE 710
711. SE 711
712. SE 712
713. SE 713
714. SE 714
715. SE 715
716. SE 716
717. SE 717
718. SE 718
719. SE 719
720. SE 720
721. SE 721
722. SE 722
723. SE 723
724. SE 724
725. SE 725
726. SE 726
727. SE 727
728. SE 728
729. SE 729
730. SE 730
731. SE 731
732. SE 732
733. SE 733
734. SE 734
735. SE 735
736. SE 736
737. SE 737
738. SE 738
739. SE 739
740. SE 740
741. SE 741
742. SE 742
743. SE 743
744. SE 744
745. SE 745
746. SE 746
747. SE 747
748. SE 748
749. SE 749
750. SE 750
751. SE 751
752. SE 752
753. SE 753
754. SE 754
755. SE 755
756. SE 756
757. SE 757
758. SE 758
759. SE 759
760. SE 760
761. SE 761
762. SE 762
763. SE 763
764. SE 764
765. SE 765
766. SE 766
767. SE 767
768. SE 768
769. SE 769
770. SE 770
771. SE 771
772. SE 772
773. SE 773
774. SE 774
775. SE 775
776. SE 776
777. SE 777
778. SE 778
779. SE 779
780. SE 780
781. SE 781
782. SE 782
783. SE 783
784. SE 784
785. SE 785
786. SE 786
787. SE 787
788. SE 788
789. SE 789
790. SE 790
791. SE 791
792. SE 792
793. SE 793
794. SE 794
795. SE 795
796. SE 796
797. SE 797
798. SE 798
799. SE 799
800. SE 800
801. SE 801
802. SE 802
803. SE 803
804. SE 804
805. SE 805
806. SE 806
807. SE 807
808. SE 808
809. SE 809
810. SE 810
811. SE 811
812. SE 812
813. SE 813
814. SE 814
815. SE 815
816. SE 816
817. SE 817
818. SE 818
819. SE 819
820. SE 820
821. SE 821
822. SE 822
823. SE 823
824. SE 824
825. SE 825
826. SE 826
827. SE 827
828. SE 828
829. SE 829
830. SE 830
831. SE 831
832. SE 832
833. SE 833
834. SE 834
835. SE 835
836. SE 836
837. SE 837
838. SE 838
839. SE 839
840. SE 840
841. SE 841
842. SE 842
843. SE 843
844. SE 844
845. SE 845
846. SE 846
847. SE 847
848. SE 848
849. SE 849
850. SE 850
851. SE 851
852. SE 852
853. SE 853
854. SE 854
855. SE 855
856. SE 856
857. SE 857
858. SE 858
859. SE 859
860. SE 860
861. SE 861
862. SE 862
863. SE 863
864. SE 864
865. SE 865
866. SE 866
867. SE 867
868. SE 868
869. SE 869
870. SE 870
871. SE 871
872. SE 872
873. SE 873
874. SE 874
875. SE 875
876. SE 876
877. SE 877
878. SE 878
879. SE 879
880. SE 880
881. SE 881
882. SE 882
883. SE 883
884. SE 884
885. SE 885
886. SE 886
887. SE 887
888. SE 888
889. SE 889
890. SE 890
891. SE 891
892. SE 892
893. SE 893
894. SE 894
895. SE 895
896. SE 896
897. SE 897
898. SE 898
899. SE 899
900. SE 900
901. SE 901
902. SE 902
903. SE 903
904. SE 904
905. SE 905
906. SE 906
907. SE 907
908. SE 908
909. SE 909
910. SE 910
911. SE 911
912. SE 912
913. SE 913
914. SE 914
915. SE 915
916. SE 916
917. SE 917
918. SE 918
919. SE 919
920. SE 920
921. SE 921
922. SE 922
923. SE 923
924. SE 924
925. SE 925
926. SE 926
927. SE 927
928. SE 928
929. SE 929
930. SE 930
931. SE 931
932. SE 932
933. SE 933
934. SE 934
935. SE 935
936. SE 936
937. SE 937
938. SE 938
939. SE 939
940. SE 940
941. SE 941
942. SE 942
943. SE 943
944. SE 944
945. SE 945
946. SE 946
947. SE 947
948. SE 948
949. SE 949
950. SE 950
951. SE 951
952. SE 952
953. SE 953
954. SE 954
955. SE 955
956. SE 956
957. SE 957
958. SE 958
959. SE 959
960. SE 960
961. SE 961
962. SE 962
963. SE 963
964. SE 964
965. SE 965
966. SE 966
967. SE 967
968. SE 968
969. SE 969
970. SE 970
971. SE 971
972. SE 972
973. SE 973
974. SE 974
975. SE 975
976. SE 976
977. SE 977
978. SE 978
979. SE 979
980. SE 980
981. SE 981
982. SE 982
983. SE 983
984. SE 984
985. SE 985
986. SE 986
987. SE 987
988. SE 988
989. SE 989
990. SE 990
991. SE 991
992. SE 992
993. SE 993
994. SE 994
995. SE 995
996. SE 996
997. SE 997
998. SE 998
999. SE 999
1000. SE 1000

ADDITIONAL COMMENTS

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 14 SC07 DATA NOT AVAILABLE
 14 SC08 1A18 - ARC 3.5 19! - TANK
 14 SC09 1A18 - ARC 3.5 19! - TANK

REFERENCE INFORMATION
 SPREF 2650.0000 SQ.FT.
 REF 1250.3000
 SPREF 1250.3000
 XMRD 5.9
 YMRD 450.0000
 SCALE .5:50





FIG. 7 EFFECT OF ANGLE OF ATTACK ON ISOLATED ET LATERAL-DIRECTIONAL AEROC. CHAR.
 MACH = 5.29

52 DEGREES

52 DEGREES - 45 DEGREES - 35 DEGREES - 25 DEGREES - 15 DEGREES - 5 DEGREES.

5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100



ADJUSTED ELEVATION, FEET

31 DEGREES.

FIG. 10. ONE CYCLE IN. 31 DEGREES - 35 DEGREES - 35 DEGREES.





FIG. 10. ONE CYCLE IN. 31 DEGREES.



(SIXTY EIGHT) NO. 1774-102 IN WHICH SAWING

FIG. 6 SIDESLIP ANGLE, DEGREES
 18 SEC 14.8 - ARC 3.5 9°
 16 SEC 14.8 - ARC 3.5 9°
 12 SEC 14.8 - ARC 3.5 9°

CONFIGURATION, DESCRIPTION
 18 SEC 14.8 - ARC 3.5 9° - TAN
 16 SEC 14.8 - ARC 3.5 9° - TAN
 12 SEC 14.8 - ARC 3.5 9° - TAN

REFERENCE INFORMATION
 SEC 1 2800, 2000, 5000
 SEC 2 1800, 1200, 8000
 SEC 3 1600, 1000, 6000
 SEC 4 1400, 800, 4000
 SEC 5 1200, 600, 2000
 SEC 6 1000, 400, 1000
 SEC 7 800, 200, 500
 SEC 8 600, 200, 200
 SEC 9 400, 200, 100
 SEC 10 200, 100, 50




FIG. 7 EFFECT OF ANGLE OF ATTACK ON ISOLATED LATERAL-DIRECTIONAL AERO. CHAR.

DATA S - SYMBOL
 12. SEC: C
 13. SEC: C
 14. SEC: C

REFERENCE INFORMATION
 CONFIGURATION DESCRIPTION
 14.8 - ARC 3.5 19° - TAN
 14.8 - ARC 3.5 19° - TAN
 14.8 - ARC 3.5 19° - TAN
 ALPHA RUDER ELEVEN
 .000 4.000 .000
 .000 4.000 .000
 -.000 -.000 .000
 REF: 2600.0000 SQ.FT.
 RE: 1200.3000 N.
 XRD: 1300.3000 Y.
 YRD: 999.0000 N.
 ZRD: 400.0000 N.
 SCALE: .0100




FIG. 7 EFFECT OF ANGLE OF ATTACK ON ISOLATED ET LATERAL-DIRECTIONAL AERO. CHAR.

CONTACT: 10.29

PAGE 34

21A SE. 5148C CONFIGURATION DESCRIPTION
 DATA NOT AVAILABLE
 148 - AEC 3.5 191 - TANK
 148 - AEC 3.5 191 - TANK

REFERENCE INFORMATION
 REF. 2680.0000 SQ.FT.
 REF. 1950.3000 N.
 REF. 1950.3000 N.
 BASE 1950.3000 N.
 XRD 1950.3000 N.
 YRD 1950.3000 N.
 ZRD 400.0000 N.
 SCALE .250



SIDE FORCE COEFFICIENT, C_x

FIG. 7 EFFECT OF ANGLE OF ATTACK ON ISOLATED ET LATERAL-DIRECTIONAL AERO. CHAR.
 CADWACH : 5.29
 DRAWING NUMBER : 538
 DRAWING MOMENT COEFFICIENT, C_y (BODY AXIS)
 PAGE 35

DATA SET SYMBOL
111 SCENE 1
111 SCENE 2
111 SCENE 3

REFERENCE INFORMATION
SPEC. 2680 0000 50,57.
REF. 1700 3000
B22.5 1700 3000
Y22 900 1700 3000
Z22 400 900 1700 3000
SCALE .008

ALPHA RUDER ELEVON
4.000 .000 .000
.000 .000 .000
-4.000 .000 .000





FIG. 7 EFFECT OF ANGLE OF ATTACK ON ISOLATED LATERAL-DIRECTIONAL AERC. CHAR.

FIG. 7 EFFECT OF ANGLE OF ATTACK ON ISOLATED LATERAL-DIRECTIONAL AERC. CHAR.
SCENE 1
SCENE 2
SCENE 3
PAGE 36
.008
.004
-.004
-.008
-.012
-.014
-.016
-.018
-.020
-.022
-.024
-.026
-.028
-.030
-.032
-.034
-.036
-.038
-.040
-.042
-.044
-.046

SCENE 1
SCENE 2
SCENE 3
PAGE 32

DATA SET 5-3C
FIGURE 7
DESCRIBING
ANGLE OF ATTACK - TAN
ANGLE OF ATTACK - TAN
ANGLE OF ATTACK - TAN

A _{PhA}	RUDER	ELEVON	REFERENCE INFORMATION
4.000	.000	.000	REF 2680 3000 50 F.
.000	.000	.000	REF 3000 3000 50
-4.000	.000	.000	REF 3000 3000 50
			X ⁺
			Y ⁺
			Z ⁺
			W ⁺
			W ⁺
			SCALE .25



SIDE FORCE COEFFICIENT, C_Y

FIG. 7 EFFECT OF ANGLE OF ATTACK ON ISOLATED ET LATERAL-DIRECTIONAL AERO. CHAR.
 $C_{YAW} = 10.29$.008
 $C_{CO}_4 = 0.04$.004
 $C_{BODY_AXIS} = 0.00$.000

14.8 - ARC 3.5 1.9 - C2317E + TAN




FIG. 8 SUMMARY OF SECOND STAGE LONSTITUDINAL AERODYNAMIC CHARACTERISTICS.

PAGE 38

1948 - APR 30 1961 - 1962
SCHOOL OF APPLIED SCIENCE

1300






TABLE I. A SUMMARY OF INVESTIGATED FLOW CHARACTERISTICS.

DATA SETS - CONFIGURATION DESCRIPTION

1A1B - ARC 3.5 1B1 - CANTER : TAN
1A1B - ARC 3.5 1B1 - CANTER : TAN
1A1B - ARC 3.5 1B1 - CANTER : TAN
1A1B - ARC 3.5 1B1 - CANTER : TAN

REFERENCE INFORMATION
SOFT.
REF. 2800 1000
S2F 2800 3000
S2E 3000 3000
S2C 3000 3000
W2D 1000 3000
W2P 500 3000
SCALE 500 1000







FIG. 10 SUMMARY OF SECOND STAGE LATERAL-DIRECTIONAL AERODYNAMIC CHARACTERISTICS.

DATA SEC. CONFIGURATION DESCRIPTION
 125501: 1A18 - ARC 3.5 191 - TANK
 125502: 1A18 - ARC 3.5 191 - TANK
 125503: 1A18 - ARC 3.5 191 - TANK

REFERENCE 10 DEPARTURE
 ALPHA .000 RUDER .000 ELEVON .000 SC.FT.
 .000 .000 .000 2500.000
 .000 .000 .000 1250.320
 .000 .000 .000 1250.320
 .000 .000 .000 1250.320
 .000 .000 .000 1250.320
 .000 .000 .000 1250.320
 SCALING






FIG. 11 SUMMARY OF ISOLATED ET LATERAL-DIRECTIONAL AERODYNAMIC CHARACTERISTICS.
 PAGE 41

TABLE 18 - ARC 3.5 19: - CENTER + TANK

S/N	PARAMETRIC VALUES		DATASET	DATA SOURCE	MACH	SCALE	REFERENCE INFORMATION
	*A	*B					
1	.9,000	.1,200	E,EV3	.000	NE5012	5,300	NE5013
2					10,300		X7
3						WPP	400,000
4						WPS	400,000
5							21




FIG. 12 SUMMARY OF SECOND STAGE LONGITUDINAL CHARACTERISTICS WITH BETA VARYING.
PAGE 42




FIG. 12 SUMMARY OF SECOND STAGE LONGITUDINAL CHARACTERISTICS WITH BETA VARYING.
 PAGE 43

!A:8 - ARC 3.5 :9: - 3RB!TER + TAN
CNE50:2:

REFERENCE INFORMATION						
STATION	BETA	PARAMETRIC VALUES	DATA SOURCE	MACH	SREF	SC.FT.
C	8.000	ALPHA .000 ELEVEN	.000 DATASET NESC12 NESC14	5.300 5.300	1.95E-005	2680 3000
			DATASET NESC13	7.300	1.95E-005	2680 3000
					1.95E-005	2680 3000







FIG. 12 SUMMARY OF SECOND STAGE LONGITUDINAL CHARACTERISTICS WITH BETA VARYING.

:A18 - ARC 3.5 19! - TANK
 SYM: BE¹A
 C -8.000 ALPH_A .000 ELEVON .000 DATASET
 NESO17 NESO18
 NESO19 10300

(NESO:7)

REFERENCE INFORMATION
 SO.FT.
 REF 2620 0000
 REF 1280 0000
 XMP 979.0000
 YMP 400.0000
 ZMP 400.0000
 SCALE

DATA SOURCE	MACH	MACH	MACH	MACH
NE5018	5.300	7.300	9.300	11.300
NE5019	10.300			




FIG. 13 SUMMARY OF ISOLATED ET LONGITUDINAL CHARACTERISTICS WITH BETA VARYING.
 PAGE 45

1A:8 - ARC 3.5 : 9: - TANK

SYMBOL SETTA .0000 ALFA .0000 PARAMETRIC VALUES
C 0.000 MACH .000 DATASET .000 DATA SOURCE
REF. 2690,0000 7.300 MACH 7.300 SPEC.
SC. FT. 125.3200 10.300 DATASET 10.300 AREA
XPROP 97.6 XPROP
YPROP 100.0 YPROP
ZPROP 400.0 ZPROP
SCALE

(NE5017)







FIG. 13 SUMMARY OF ISOLATED ET LONGITUDINAL CHARACTERISTICS WITH BETA VARYING.

PAGE 46

1A:8 - ARC 3.5 191 - TANK

SYMBOL	SE/IA	PARAMETRIC VALUES			DATASET	MACH	DATA SOURCE	MACH	REF	REFERENCE INFORMATION
		ALPHA	ELEV	.000						
C	8.000									N.
										N.
										X
										Y
										Z
										27
										SCALE
										400 3000 .2100







FIG. 13 SUMMARY OF ISOLATED ET LONGITUDINAL CHARACTERISTICS WITH BETA VARYING.
PAGE 47

APPENDIX
TABULATED SOURCE DATA

**Tabulations of plotted data are available on request
from Data Management Services.**

DATE 06 MAR 75

TABULATED SOURCE DATA - ARC 3.5 191 (IA16)

PAGE 1

TA18 - ARC 3.5 191 - ORBITER + TANK

(RES001) (21 FEB 75)

REFERENCE DATA

SPAN = 2890.000 SQ.FT. WIND = 97.9 IN.YT
 LIFT = 1290.390 IN. DRAG = 400.000 IN.YT
 DRAF = 1290.390 IN. SCALE = .0100

PARAMETRIC DATA

BETA = ELEV = .000
 ROLL = .000
 PITCH = .000

RUN NO. 0/0 ROLL = 2.65

	MACH	ALPHA	BETA	CN	CD	CAF	CLW	CY	CB
GRADIENT	5.289	-8.648	-.019952	-.26179	-.04952	.21256	.11164	.01453	-.00556
	5.289	-6.416	-.029350	-.21198	-.03694	.19660	.09670	.01434	-.00517
	5.289	-4.539	-.06954	-.17125	-.04933	.16931	.08547	.01395	-.00569
	5.289	-2.284	-.06986	-.12273	-.03987	.17522	.06286	.01329	-.00584
	5.289	-1.165	-.05717	-.07496	-.03702	.16320	.04692	.01214	-.00568
	5.289	1.900	-.03625	-.02026	-.03560	.15558	.03046	.01176	-.00578
	5.289	3.901	-.04950	-.01560	-.03313	.14912	.01658	.01151	-.00574
	5.289	6.950	-.04497	-.06441	-.03095	.14259	.00704	.00743	-.00532
	5.289	8.992	-.04219	-.10916	-.02834	.13633	.01563	.00993	-.00526
	5.289	10.220	-.04538	-.15695	-.02751	.13352	.03438	.00987	-.00526
	5.289	15.493	-.03229	.29147	-.03054	.12640	.05821	.00787	-.00499
	5.289	20.818	-.05603	.44703	-.02534	.12356	.13718	.00231	-.00477
	5.289	25.509	-.03164	.59194	-.03554	.12533	.16918	.00881	-.00898
	5.289	29.320	-.06891	.74894	-.04072	.12354	.25988	.01182	-.00847
	GRADIENT	.00134	.02222	.00988	-.00437	-.00760	-.00000	-.00000	-.00000

RUN NO. 0/0 ROLL = 2.74

	MACH	ALPHA	BETA	CN	CD	CAF	CLW	CY	CB
GRADIENT	7.320	-6.464	-.03124	-.20911	-.04069	.21768	.09497	.01458	-.00614
	7.320	-6.250	-.02935	-.19099	-.03645	.20369	.08965	.01361	-.00529
	7.320	-4.384	-.03050	-.15614	-.03637	.16556	.06885	.01292	-.00528
	7.320	-2.142	-.02937	-.10950	-.03695	.18221	.05136	.01176	-.00525
	7.320	-0.924	-.02875	-.06144	-.03159	.17241	.03764	.00933	-.00446
	7.320	1.913	-.02821	-.01950	-.03000	.16444	.02697	.00822	-.00435
	7.320	3.851	-.02612	-.01535	-.02220	.15575	.01874	.00743	-.00425
	7.320	5.970	-.02256	.05774	-.02337	.14969	.00993	.00664	-.00405
	7.320	8.012	-.02155	.10041	-.02220	.14281	.00461	.00650	-.00404
	7.320	10.106	-.02060	.14274	-.02099	.13776	.11358	.00395	-.00325
	7.320	15.284	-.01985	.26324	-.01821	.12795	.05436	.00187	-.00213
	7.320	20.418	-.01692	.30645	-.01517	.12222	.09683	.00233	-.00350
	7.320	24.893	-.01789	.36722	-.01846	.16835	.15945	.00368	-.00307
	7.320	26.357	-.01759	.38736	-.01984	.12098	.21696	.00562	-.00495
	GRADIENT	.00069	.02092	.00130	-.00474	-.00612	-.00014	-.00011	-.00000

REFERENCE DATA

SHT = 2899.0000 90. FT. XRP = 979.0000 IN. XT
 LFT = 1299.3000 IN. YRP = .9995 IN. YT
 BFT = 1299.3000 IN. ZRP = 495.0000 IN. ZT
 SCALE = .0100

	RUN NO.	0/ 0	RWL = 1.92	GRADIENT INTERVAL = -5.00/ 5.00
MACH	ALPHA	BETA	CN	CF
10.299	-.03109	-.21082	-.04867	.21299
10.299	-6.269	-.02981	-.18656	.04676
10.299	-4.401	-.02965	-.15977	-.0583
10.299	-2.292	-.02551	-.11453	-.03391
10.299	-126	-.02338	-.07299	-.03495
10.299	1.811	-.05933	-.03819	-.02743
10.299	3.771	-.01763	-.00973	-.02567
10.299	5.841	-.01089	-.03341	-.01615
10.299	7.903	-.01325	-.03854	-.01177
10.299	9.953	-.00751	-.11719	-.01231
10.299	15.048	-.05426	.28936	-.05553
10.299	20.154	-.00332	.35007	-.00692
10.299	24.611	-.05293	.49308	-.04443
10.299	28.241	-.05227	.51906	-.00337
GRADIENT		.00153	.01953	.00261

TA18 - ARC 3.5 191 - ORBITER + TANK

REFERENCE DATA

SHT = 2899.0000 90. FT. XRP = 979.0000 IN. XT
 LFT = 1299.3000 IN. YRP = .9995 IN. YT
 BFT = 1299.3000 IN. ZRP = 495.0000 IN. ZT
 SCALE = .0100

	RUN NO.	0/ 0	RWL = 3.18	GRADIENT INTERVAL = -5.00/ 5.00
MACH	ALPHA	BETA	CN	CF
5.291	-.7.741	.04274	.28844	-.57015
5.291	-5.837	.03928	.19740	-.05987
5.291	-3.785	.03571	.09174	-.00339
5.291	-1.911	.03242	.08287	-.05358
5.291	.030	.03199	-.00583	.00349
5.291	1.945	.03845	-.07751	.0194
5.291	3.812	.04053	-.11597	.03524
5.291	5.819	.03120	-.16876	.05472
5.291	7.837	.03969	-.22772	.07481
GRADIENT		.00382	.02617	.00859

(RES01) (21 FEB 75)

PARAMETRIC DATA

BETA = .000 RUDER = .000
 ELEVON = .000

(RES02) (21 FEB 75)

PARAMETRIC DATA

ALPHA = 4.000 RUDER = .000
 ELEVON = .000

DATE 08 MAR 75

TABULATED SOURCE DATA - ARC 3.5 191 (1A18)

PAGE 3

1A18 - ARC 3.5 191 - ORBITER + TANK

REFERENCE DATA

SREF = 2895.00000 SQ.FT.
 LAT = 129.3000 IN.
 DREF = 1295.3000 IN.
 SCALE = .0000

XRP = 979.0000 IN. XT
 YRP = .0000 IN YT
 ZRP = 400.0000 IN. ZT

PARAMETRIC DATA

RUN NO.	D/ G	RVL =	2.70	GRADIENT INTERVAL = -5.00/ 5.00			
				CN	CY	CB	CA
MACH	BETA						CLW
7.320	-7.795	.03276	.18932	-.05277	.02598	3.98618	.16158
7.320	-5.890	.03124	.13044	-.03705	.01789	3.98001	.15898
7.320	-3.381	.02217	.08925	-.02205	.01052	3.98735	.15859
7.320	-1.947	.02346	.03728	-.00939	.00471	3.99267	.15456
7.320	-.005	.02886	-.00577	.00149	-.00198	3.99294	.15692
7.320	1.966	.02098	-.05396	.01453	-.00811	3.99404	.15607
7.320	3.929	.03093	-.10270	.02792	-.01511	3.99447	.15912
7.320	5.946	.03331	-.15682	.04347	-.02284	3.99442	.16159
7.320	7.799	.04152	-.21245	.06084	-.03119	3.99554	.16443
GRADIENT	.00009	-.02341	.00633	-.00329	.00080	.00034	-.00049
MACH	BETA						CLW
10.290	-7.806	.02153	.15397	-.04211	.01953	3.99555	.16309
10.290	-5.943	.01029	.10821	-.02885	.01388	3.98352	.15702
10.290	-3.692	.01703	.06975	-.01742	.00901	3.98955	.15127
10.290	-1.910	.00585	.02728	-.00632	.00317	3.98656	.14754
10.290	-.947	.01322	-.01974	.00192	-.00182	3.99043	.14754
10.290	2.054	.01925	-.05137	.01188	-.00759	3.99286	.14807
10.290	3.929	.02469	-.09337	.02298	-.01375	3.99469	.15083
10.290	5.967	.02873	-.14051	.03772	-.02078	3.99501	.15444
10.290	7.824	.03453	-.18657	.05123	-.02737	3.99573	.15813
GRADIENT	.00143	-.02955	.00595	-.00287	.00072	-.00072	-.00049

(RES02) (21 FEB 75)

DATE 08 MAR 75

TABULATED SOURCE DATA - ARC 3.5 191 (IA18)

PAGE 4

(RES003) (21 FEB 75)

REFERENCE DATA

SREF = 2690.0000 50. FT. XREF = 979.0000 IN. XT
 LREF = 1290.3000 IN. YREF = .0000 IN. YT
 BREF = 1290.3000 IN. ZREF = 499.0000 IN. ZT
 SCALE = .0100

PARAMETRIC DATA

ALPHA = .000 ROLLER = .000
 ELEVON = .000

IA18 - ARC 3.5 191 - ORBITER + TANK

RUN NO.	0/ 0	RVAL = 3.08	GRADIENT INTERVAL = -5.00/ 5.00						
MACH	BETA	CN	CF	CYN	CBL	ALFA	CAF	CLM	
5.291	-7.714	-.06545	.22478	-.07716	.05065	-.22754	.19991	.03635	
5.291	-5.831	-.06538	.16273	-.05489	.02245	-.21617	.18689	.03922	
5.291	-3.793	-.06583	.10589	-.05349	.01382	-.20897	.17910	.04022	
5.291	-1.896	-.06599	.04413	-.05148	.00562	-.20158	.17222	.04883	
5.291	-0.910	-.06539	.05803	-.05260	.00143	-.19560	.16723	.04013	
5.291	1.930	-.06599	.05594	-.05088	.00985	-.19037	.17057	.03557	
5.291	5.757	-.05743	.08494	.06195	.02669	-.18713	.17849	.03229	
5.291	7.150	-.04283	.24559	.18486	.03570	-.18421	.18316	.02740	
GRADIENT	.05122	-.02900	.05942	.05419	.00324	-.00160	-.00353	-.00353	
RUN NO.	0/ 0	RVAL = 2.04	GRADIENT INTERVAL = -5.00/ 5.00						
MACH	BETA	CN	CF	CYN	CBL	ALFA	CAF	CLM	
7.320	-7.850	-.05610	.19897	-.06326	.02893	-.11192	.18693	.02989	
7.320	-5.922	-.05974	.11449	-.04410	.05830	-.10830	.18692	.03329	
7.320	-3.879	-.05963	.06616	.02487	.05928	-.10385	.17376	.03433	
7.320	-1.914	-.05953	.03723	-.01049	.05414	-.10155	.17229	.03481	
7.320	.027	-.05741	.01192	.02669	.00197	-.09889	.17024	.03457	
7.320	1.983	-.05388	.056504	.05758	.00995	-.09977	.16890	.03329	
7.320	3.939	-.05081	.11610	.03360	.01641	-.09450	.17370	.03217	
7.320	5.936	-.04437	.17136	.05155	.02437	-.09374	.17799	.02693	
7.320	7.158	-.04000	.23053	.07183	.03285	-.05414	.18253	.02382	
GRADIENT	.05119	-.02595	.00742	.00341	.00125	-.00093	-.00039	-.00039	
RUN NO.	0/ 0	RVAL = 1.73	GRADIENT INTERVAL = -5.00/ 5.00						
MACH	BETA	CN	CF	CYN	CBL	ALFA	CAF	CLM	
10.291	-7.919	-.05440	.17258	-.05277	.02212	-.07032	.17843	.03172	
10.291	-5.957	-.05291	.12278	-.03705	.01502	-.06727	.17274	.03158	
10.291	-3.955	-.05631	.06987	-.02394	.01042	-.06599	.16724	.03435	
10.291	-1.963	-.05026	.03147	-.00616	.00326	-.06285	.16452	.03102	
10.291	.006	-.05324	.01945	.00327	.00193	-.06224	.16378	.03406	
10.291	1.995	-.04536	.05918	.01684	-.00897	-.05963	.16469	.02956	
10.291	3.931	-.04172	.10807	.03562	-.01584	-.05790	.16891	.02876	
10.291	5.969	-.04142	.15858	.04651	-.02260	-.05990	.17315	.02944	
10.291	7.060	-.04324	.21299	.06413	-.03960	-.06139	.17336	.02994	
GRADIENT	.05114	-.02387	.00674	-.00330	.00125	-.00099	-.00039	-.00039	

DATE 08 MAR 75

TABULATED SOURCE DATA - ARC 3.5 191 (IA16)

PAGE 3

T1A16 - ARC 3.5 191 - ORBITER + TMA

(RES004) (21 FEB 72)

REFERENCE DATA

XDP = 2000.0000 IN. FT. **ZDP =** 979.0000 IN. XT
YDP = 1297.3000 IN. **YTP =** .0000 IN. YT
BDF = 1299.3000 IN. **ZDP =** 400.0000 IN. ZT
SCALE = .5109

RUN NO. D/ G RVAL = 3.13

GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	CN	CY	CYN	CL	ALPHA	CAF	CLW
5.291	-7.632	-.16032	.24596	-.06796	.05393	-4.40391	.21655	.97091
5.291	-5.751	-.15988	.17691	-.06194	.02374	-4.39758	.20674	.97133
5.291	-3.767	-.15847	.11059	-.03776	.01442	-4.38651	.19945	.97155
5.291	-1.893	-.15689	.05062	-.01719	.00636	-4.38128	.19257	.97136
5.291	.096	-.15694	.06949	.05344	-.01818	-4.37785	.18817	.97038
5.291	1.955	-.15225	.07254	.02201	-.03048	-4.37297	.19170	.95959
5.291	3.803	-.15239	.13729	.04795	-.01978	-4.37483	.19488	.95242
5.291	5.798	-.14798	.21064	.07335	-.02993	-4.37489	.20334	.95571
5.291	7.653	-.14199	.28167	.10247	-.03993	-4.37489	.20512	.95210
GRADIENT		.00266	.03247	.0122	.00449	.00182	-.00055	-.00032

RUN NO. D/ G RVAL = 2.35

GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	CN	CY	CYN	CL	ALPHA	CAF	CLW
7.320	-7.814	-.14530	.21896	-.07470	.02776	-4.19556	.20236	.95991
7.320	-5.910	-.14650	.16134	-.05473	.01999	-4.19239	.19845	.95256
7.320	-3.889	-.14945	.10331	-.03469	.01222	-4.19317	.19709	.95482
7.320	-1.942	-.14442	.04697	-.01635	.00545	-4.18693	.19421	.95348
7.320	-0.12	-.14506	.05636	.01187	-.00149	-4.18771	.19139	.95374
7.320	1.982	-.14276	.06670	.02115	-.00325	-4.18405	.19473	.95433
7.320	3.923	-.14420	.12684	.04052	-.01711	-4.18583	.19676	.95465
7.320	5.913	-.14271	.18444	.05632	-.02529	-4.18736	.20098	.95339
7.320	7.796	-.13921	.24666	.08223	-.03415	-4.18855	.20539	.95267
GRADIENT		.00262	.02326	.00633	-.00375	.00091	-.00050	-.00051

RUN NO. D/ G RVAL = 1.45

GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	CN	CY	CYN	CL	ALPHA	CAF	CLW
10.290	-7.869	-.13463	.18996	-.06148	.02184	-4.12461	.20205	.95932
10.290	-5.882	-.13782	.12847	-.04293	.01418	-4.12341	.19592	.95127
10.290	-3.899	-.13741	.07527	-.02424	-.00771	-.00771	-.00771	-.00771
10.290	-1.956	-.13915	.03068	-.00998	.00225	-4.11545	.18945	.95956
10.290	-0.1395	-.13955	.01737	.05538	-.00288	-4.11599	.18705	.95292
10.290	2.046	-.13229	.06648	.02488	-.00891	-4.11441	.18747	.95338
10.290	3.946	-.12971	.11643	.03637	-.02524	-4.11370	.19146	.95775
10.290	5.963	-.12994	.15946	.05545	-.02514	-4.11080	.19198	.95810
10.290	7.818	-.11129	.21205	.06885	-.02742	-4.15978	.19906	.95225
GRADIENT		.00106	.02443	.00767	-.00284	-.00079	-.00032	-.00025

DATE 08 MAR 75

TABULATED SOURCE DATA - ARC 3.5 191 (IA10)

PAGE 6

IA10 - ARC 3.5 191 - ORBITER + TANK

(RES005) (21 FEB 75)

REFERENCE DATA

SREF = 2890.0000 59.FT. XRP = 979.0000 IN. XT
 LREF = 1250.3000 IN. YRP = .0000 IN YT
 BREF = 1250.3000 IN. ZRP = 400.0000 IN. ZT
 SCALE = .0100

RUN NO. 17/ 0 RWL = 2.99 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	CN	CF	CLM	CM	CB
7.320	15.844	-.00259	.26427	-.00221	.12668	-.006184	-.000229
7.320	20.361	.00036	.39134	-.00168	.11969	-.00625	-.000358
7.320	25.551	-.50125	.57939	-.00091	.11853	-.00758	-.00024
7.320	30.711	.00120	.79215	.00132	.12118	-.26865	.00131
7.320	35.218	.00194	.98846	.00362	.12363	-.35394	.00196
7.320	38.901	.00326	1.13934	.00498	.12692	-.41800	.00223
GRADIENT		.00050	.00000	.00000	.00000	.00000	.00000

IA10 - ARC 3.5 191 - TANK

(RES006) (21 FEB 75)

REFERENCE DATA

SREF = 2890.0000 59.FT. XRP = 979.0000 IN. XT

LREF = 1250.3000 IN. YRP = .0000 IN YT

BREF = 1250.3000 IN. ZRP = 400.0000 IN. ZT

SCALE = .0100

RUN NO. 0/ 0 RWL = 3.11 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	CN	CF	CLM	CM	CB
5.289	-30.218	-.90338	-.62224	.00023	.17167	.14777	.00119
5.289	-24.825	-.90772	-.46556	.00079	.15295	.10440	.00061
5.289	-20.401	-.90892	-.35078	-.00170	.13241	.06937	-.00277
5.289	-14.732	-.91076	-.22533	.00416	.11140	.03464	-.00221
5.289	-10.179	-.91058	-.14280	-.00516	.09115	.01840	-.00165
5.289	-6.192	-.91019	-.11020	-.00476	.09853	.01341	-.00166
5.289	-5.129	-.91053	-.07929	-.00545	.09571	.01054	-.00147
5.289	-4.022	-.90997	-.05218	-.00555	.09527	.00860	-.00115
5.289	-2.039	-.91177	-.02920	-.00725	.09269	.00781	-.00099
5.289	.974	-.91248	-.01412	-.00801	.09285	.00801	-.00086
5.289	2.185	-.91159	-.00923	-.00791	.09103	.00912	-.00052
5.289	4.157	-.91203	.04319	-.00664	.09009	.00759	-.00023
5.289	6.164	-.91231	.26737	-.00984	.08977	.00682	-.00016
5.289	6.181	-.91256	.09459	-.01558	.08975	.01461	-.00127
GRADIENT		-.90008	.01168	-.00035	-.00058	-.00067	-.00000

PARAMETRIC DATA

BETA = .000 ELEVON = .000

DATE 06 MAR 73

TABULATED SOURCE DATA - ARC 3.5 191 (IA10)

IA10 - ARC 3.5 191 - TANK

REFERENCE DATA

REFP = 2690.0000 50. FT. **XRP =** 979.0000 IN. XT
LREF = 1290.3000 1%. **YRP =** .0000 IN. YT
BREF = 1290.3000 IN. **ZRP =** 460.0000 IN. ZT
SCALE = .0100

RUN NO. DV D RIVL = 3.0 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	CN	CF	CM	CQH	CYN	CBL
7.320	-30.176	.00242	-.61317	.01698	.17687	.14628	-.00779	.00146
7.320	-24.560	.00229	-.46549	.01169	.15959	.10411	-.00694	.00063
7.320	-20.403	.00255	-.35598	.00588	.13854	.06566	-.00625	.00030
7.320	-14.795	.00112	-.21520	.00339	.11992	.02733	-.00245	.00018
7.320	-10.326	.00022	-.13542	.00174	.10466	.01158	-.00105	.00011
7.320	-8.294	.00120	-.10551	.00055	.10073	.00758	-.00092	.00011
7.320	-6.290	.00139	-.07865	-.00011	.09777	.00547	-.00067	.00009
7.320	-4.168	.00016	-.05205	.00053	.09513	.00458	-.00036	.00002
7.320	-2.132	.00207	-.02782	-.00150	.09410	.00445	-.00039	.00001
7.320	-.095	.00338	-.00476	-.00217	.09393	.00364	-.00067	.00000
7.320	1.976	.00276	.01637	-.00217	.09275	.00275	-.00053	.00001
7.320	3.973	.00300	.03710	-.00253	.0914	.00180	-.00023	.00003
7.320	5.964	.00164	.08417	-.00125	.09066	.00083	-.00022	.00001
7.320	7.958	-.00286	.08828	-.00240	.09333	.00743	-.00032	.00001
GRADIENT	-.00031	.01092	-.00033	-.00026	.00054	.00051	-.00009	.00001

RUN NO. DV D RIVL = 1.61 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	CN	CF	CM	CQH	CYN	CBL
10.289	-21.963	-.00166	-.59459	.01636	-.1136	.15360	-.01169	.00160
10.289	-24.389	-.00016	-.44443	.01251	-.15716	.1487	-.00687	.00095
10.289	-20.247	-.00254	-.32252	.00231	-.11116	.06927	-.00420	.00045
10.289	-14.703	-.00234	-.19082	-.00195	-.09124	.02213	-.00214	.00027
10.289	-10.216	-.00033	-.11950	.00060	-.09124	.00561	-.00070	.00016
10.289	-8.231	-.00195	-.09041	-.00122	-.29111	.00262	-.00057	.00015
10.289	-6.237	-.00175	-.05585	-.00378	-.08745	.00048	-.00002	.00013
10.289	-4.139	-.00072	-.03626	-.00205	-.08645	.00010	-.00026	.00015
10.289	-2.151	-.00054	-.02521	-.00112	-.08663	.00231	-.00003	.00014
10.289	-.056	-.00035	-.01195	-.00103	-.08593	.00337	-.00010	.00014
10.289	1.985	-.00118	-.01712	-.00280	-.08569	.0017	-.00011	.00009
10.289	3.920	-.00170	-.03462	-.00365	-.08531	.01560	-.00002	.00010
10.289	5.920	-.00162	-.05414	-.00358	-.08561	.1781	-.00001	.00011
10.289	7.871	-.00122	.08256	-.00235	-.08741	.1781	-.00008	.00013
GRADIENT	-.00013	.00029	-.00025	-.00015	-.00015	-.00002	-.00002	-.00001

REFERENCE DATA

REFP = .0000 E+000 **XRP =** .0000 E+000
LREF = .0000 E+000 **YRP =** .0000 E+000
BREF = .0000 E+000 **ZRP =** .0000 E+000

ELEVON = .0000 E+000**Rudder =** .0000 E+000**BETA =** .0000 E+000**ELMCH =** .0000 E+000**GRADIENT =** .0000 E+000

PAGE 7

(REFS6) (21 SEP 75)

DATE 28 MAR 75

TABULATED SOURCE DATA - ARC 3.5 191 (IA16)

PAGE 8

1A16 - ARC 3.5 191 - TANK

REFERENCE DATA

SUPER = 2800.0000 92.FT. XREF = 979.0000 IN. XT
 LREF = 1200.3000 IN. YREF = 0.0000 IN. YT
 BREW = 1200.3000 IN. ZREF = 400.0000 IN. ZT
 SCALE = .0100

RUN NO. 11/ 9 RVL = 2.59 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	ALPHA	CN	CF	CM	CN	CB
7.320	-7.919	4.04999	.94253	.99145	.09330	.00394	.00015
7.320	-5.949	4.04735	.94321	.99242	.09619	.00351	.00015
7.320	-3.899	4.04676	.94105	.94236	.09122	.00688	.00258
7.320	-1.955	4.05308	.94758	.92038	.09753	.00143	.00014
7.320	-1.938	4.05211	.94441	.90177	.09006	.00826	.00013
7.320	2.064	4.04963	.94375	.92495	.09953	.00173	.00003
7.320	3.978	4.04937	.94378	.94644	.09112	.00716	.00004
7.320	6.916	4.04924	.94402	.97242	.09100	.00626	.00012
7.320	7.886	4.04778	.94993	.99754	.09126	.00599	.00019
GRADIENT	.00013	.00101	.01123	.00005	.00001	.00003	.00002

RUN NO. 8/ 9 RVL = 1.52 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	ALPHA	CN	CF	CM	CN	CB
10.295	-7.970	4.02704	.04215	.98022	.08837	.00520	.00020
10.295	-5.992	4.02648	.03941	.95295	.02731	.00455	.00020
10.295	-3.922	4.02731	.04010	.03327	.08501	.00650	.00012
10.295	-1.940	4.02571	.03822	.01302	.08437	.00675	.00004
10.295	-1.903	4.02722	.03911	.00680	.08493	.00600	.00048
10.295	2.022	4.02717	.03890	.02714	.98480	.01885	.00244
10.295	4.020	4.02882	.04288	.05084	.08583	.00651	.00030
10.295	6.059	4.02676	.04098	.07213	.08597	.00551	.00003
10.295	7.935	4.02847	.04104	.09053	.09227	.00522	.00003
GRADIENT	.00016	.00032	.01070	.00001	.00001	.00002	.00002

(REF007) (21 FEB 75)

PARAMETRIC DATA

ALPHA = 4.000
 ELEVON = .000
 RUDER = .000

IA16 - ARC 3.5 191 - TANK

(RESPONSE) (21 FEB 75)

REFERENCE DATA

SQ.FT = 2855.0000 SQ.FT. XRP = 979.0000 IN. XT
 LRF = 1255.3000 IN. YRP = .0000 IN. YT
 RRP = 1255.3000 IN. ZRP = 499.0000 IN. ZT
 SCALE = .0100

PARAMETRIC DATA

ALPHA = .000
 ELEVON = .000
 RUDDER = .000

RUN NO. D/ G RAVL = 3.52 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	CN	CY	CLW	CN	CB	ALPHA	CAF
5.289	-7.834	-.00276	.10394	.00046	.00049	.00027	.02401	.00393
5.289	-5.952	-.00361	.07623	.00066	.00055	.00011	.02162	.00413
5.289	-3.915	-.00365	.04828	.00014	.00016	.00006	.01997	.00416
5.289	-1.929	-.00367	.02322	.00056	.00069	.00006	.01835	.00330
5.289	.001	-.00353	.00058	.00033	-.00034	.00002	.01646	.00331
5.289	2.033	-.00462	-.02410	.00034	-.00144	-.00018	.01917	.00215
5.289	3.939	-.00368	-.04841	.00078	-.00165	-.00033	.01913	.00095
5.289	5.999	-.00357	-.07336	.00078	-.00075	-.00028	.01676	.00993
5.289	7.897	-.00468	-.10321	.00065	.00161	-.00048	.01352	.00869
GRADIENT	.00005	-.01224	-.00014	.00038	-.00005	-.00005	-.00005	-.00005

RUN NO. D/ G RAVL = 2.16 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	CN	CY	CLW	CN	CB	ALPHA	CAF
7.320	-7.950	.00005	.00348	.00055	.00064	.00016	.00069	.00723
7.320	-6.933	.00176	.06966	.00080	.00133	.00007	.01056	.00683
7.320	-3.898	-.00085	.04467	.00062	.00096	.00005	.00831	.00335
7.320	-1.917	-.00034	.02144	.00045	.00224	.00005	.00843	.00318
7.320	.009	-.00129	-.00023	.00044	-.00025	.00008	.01092	.00410
7.320	3.982	-.00211	-.04823	.00084	-.00374	-.00014	.01084	.00216
7.320	6.947	-.00213	-.07245	.00082	.00396	.00026	.00922	.00447
7.320	7.914	-.00214	-.09720	.00115	.00332	.00032	.00815	.00414
GRADIENT	.00037	-.01177	.00055	.00099	-.00052	.00035	-.00057	-.00057

RUN NO. D/ G RAVL = 1.51 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	CN	CY	CLW	CN	CB	ALPHA	CAF
10.299	-6.927	-.00469	.07920	.00434	.00573	.00021	.15226	.00035
10.299	-6.104	-.00196	.06729	.00341	.00524	.00020	.15292	.00090
10.299	-2.099	-.00072	.01531	.00321	.00221	.00004	.15313	.00853
10.299	-1.103	-.00267	-.05636	.00297	.00296	.00003	.15187	.00335
10.299	1.901	-.00213	-.02569	.00294	.00239	.00001	.15427	.00897
10.299	3.893	-.00375	-.04066	.00373	.00436	-.00003	.15113	.00825
10.299	5.959	-.00227	-.07749	.00280	.00555	-.00003	.15188	.00770
10.299	7.871	-.00631	-.09174	.00314	.00561	-.00002	.15019	.00816
GRADIENT	-.00031	-.01099	.00038	-.00111	-.00001	-.00001	-.00016	-.00016

REFERENCE DATA

SHEP = 2000.0000 IN. FT.
LADP = 1220.3000 IN.
SHDP = 1229.3000 IN.
SCALZ = .0100

WIND = 400.0000 IN. ZT
IN AT = 0.0000
IN ZT = 0.0000

RUN NO. 9/ 9 RWL = 3.04 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	CN	CY	CM	CN	CY	CM	CL	CD	ALPHA	CAF
5.289	-7.870	-.96193	.10413	.01086	-.01143	.00959	-.00163	.005562	.00774		
5.289	-5.938	-.95930	.07319	.00962	-.00944	.00441	-.00440	.005440	.00730		
5.289	-3.892	-.95652	.04732	.00964	.00026	.00028	-.00027	.005207	.00712		
5.289	-1.915	-.95172	.02252	.00913	-.00211	.00018	-.00018	.005074	.00611		
5.289	-.001	-.95357	-.00226	.00832	-.00064	.00000	-.00000	.005098	.00504		
5.289	2.027	-.95122	-.02539	.00869	-.00152	.00005	-.00005	.005081	.00449		
5.289	3.949	-.95393	-.00571	.00914	-.00181	.00017	-.00017	.004961	.00380		
5.289	6.010	-.95693	-.00934	.00667	-.00268	-.00023	-.00023	.005251	.00323		
5.289	7.895	-.95823	-.10848	.00929	.00144	-.00044	-.00044	.005249	.00333		
GRADIENT		.00010	-.01246	.00004	-.00026	-.00006	-.00006	.00025	-.00042		

RUN NO. 9/ 9 RWL = 2.75 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	CN	CY	CM	CN	CY	CM	CL	CD	ALPHA	CAF
7.320	-7.943	-.91174	.00794	.00996	.00272	.00133	-.00133	.005845	.00025		
7.320	-5.934	-.00435	.07187	.00493	.00269	.00021	-.00021	.005688	.00018		
7.320	-3.871	-.00664	.05507	.00193	.0012	-.0012	-.0012	.005667	.00012		
7.320	-1.911	-.00734	.02301	.00386	.00098	.00002	-.00002	.005683	.00005		
7.320	-.002	-.04933	.00075	.05383	-.00034	.00003	-.00003	.005625	.00003		
7.320	2.017	-.04804	-.02424	.00368	-.00266	-.00004	-.00004	.005626	.00002		
7.320	3.977	-.04658	-.04645	.00391	-.00330	-.00004	-.00004	.005663	.00002		
7.320	6.027	-.04902	-.07688	.00374	-.00401	-.00018	-.00018	.005704	.00007		
7.320	7.911	-.05133	-.09774	.00463	-.00336	-.00024	-.00024	.005721	.0003		
GRADIENT		.00023	-.01184	-.00113	-.00172	-.00008	-.00008	-.00026	-.00036		

RUN NO. 9/ 9 RWL = 1.42 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	CN	CY	CM	CN	CY	CM	CL	CD	ALPHA	CAF
10.290	-7.977	-.04794	.08096	.00430	.00511	.00339	-.00339	.00662	.00445		
10.290	-6.001	-.04802	.05662	.00223	.00484	.0021	-.0021	.01879	.00288		
10.290	-3.898	-.04538	.03574	.00192	.00404	.00020	-.00020	.02593	.00036		
10.290	-1.917	-.03897	.01628	.00069	.00236	.00002	-.00002	.02335	.00030		
10.290	-.953	-.04158	-.00110	.00166	.00066	.00002	-.00002	.02337	.00030		
10.290	2.072	-.04837	-.02277	.00884	-.00153	-.00002	-.00002	.02358	.00036		
10.290	4.939	-.04998	-.04259	.00869	-.00054	-.00002	-.00002	.02354	.00036		
10.290	6.063	-.04359	-.07044	.00194	-.00373	-.00002	-.00002	.02356	.00033		
10.290	7.973	-.05097	-.05392	-.00112	-.00069	-.00003	-.00003	.02358	.00036		
GRADIENT		.00032	-.01558	-.00112	-.00072	-.00008	-.00008	-.00026	-.00036		

(RES00) (21 FEB 75)

PARAMETRIC DATA

DATE 26 MAR 75

TABULATED SOURCE DATA - ARC 3.5 191 (1A16)

PAGE 11

1A18 - ARC 3.5 191 - ORBITER + TANK

(RES010) (21 FEB 75)

REFERENCE DATA

$XRP = 2000.0000$ 59. FT.
 $YRP = 979.0000$ IN. XT
 $ZRP = 1250.3000$ IN.
 $SCALE = .0100$

RUN NO. 20/ 9 RVL = 2.95

GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	CAB-O	CAB-T	ALPHA	CN	CY	CA	CM	CN	CY	CA	CM
5.291	-7.743	-.00631	-.00752	-.00777	.23219	.05313	.05659	.03659	-.00459	.03494	.04227	.02492
5.291	-5.058	-.00949	-.00933	-.01105	-.00831	.16372	.05570	.03977	-.00857	.01618	.04266	.01618
5.291	-3.634	.00289	-.00207	-.00207	-.00854	.10275	.06386	.04251	-.00851	.03803	.04251	.00825
5.291	-1.975	.00416	.00103	-.01659	-.08689	.04796	.07035	.03396	-.00826	.00925	.04491	.00925
5.291	-.559	.00474	.00470	-.01639	-.08354	.00753	.07966	.04491	-.00826	.00925	.04227	.01123
5.291	1.938	.00993	.00334	-.01614	-.07789	.06610	.08942	.04227	-.00832	.01610	.03940	.01610
5.291	3.794	.00938	.00302	-.016349	-.07226	.12039	.00337	.00337	-.00832	.02552	.03413	.02552
5.291	5.782	.00992	.00199	-.016652	-.05973	.12648	.03413	.03413	-.00826	.03542	.02884	.03542
5.291	7.573	.00996	.00286	-.017335	-.04604	.24507	.16233	.00481	-.00822	.00995	.04491	.00995
GRADIENT		.00028	.00016	-.00085	.00217	-.02918	-.0043	-.0043	-.00822			

1A19 - ARC 3.5 191 - ORBITER + TANK

(RES011) (21 FEB 75)

REFERENCE DATA

$XRP = 2000.0000$ 59. FT.
 $YRP = 979.0000$ IN. XT
 $ZRP = 1250.3000$ IN.
 $SCALE = .0100$

RUN NO. 19/ 9 RVL = 2.65

GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	CAB-O	CAB-T	BETA	CN	CY	CA	CM	CN	CY	CA	CM
5.289	-6.648	-.00417	-.00835	-.05982	-.26979	-.04052	.21634	.10955	.01453	.03856		
5.289	-6.416	.00003	.00893	-.05649	-.21198	-.03894	.20558	.09671	.01434	.03117		
5.289	-4.539	.00258	.00955	-.06054	-.17125	-.04033	.19764	.08102	.01395	.02569		
5.289	-2.284	.00370	.00663	-.06889	-.12273	-.03957	.16687	.06383	.01309	.02564		
5.289	-.65	.00288	.00571	-.05717	-.07496	-.03702	.17710	.04713	.01214	.02568		
5.289	1.907	.00953	.00913	-.05426	-.02826	-.03540	.16924	.03164	.01176	.02573		
5.289	3.901	.00476	.00870	-.04669	.01569	-.03313	.16258	.01792	.01151	.02574		
5.289	6.630	.00536	.00882	-.04467	-.06441	-.03095	.15617	.02154	.01043	.02532		
5.289	8.692	.00585	.00759	-.04219	-.10916	-.02834	.15128	.01421	.00993	.02528		
5.289	10.220	.00559	.00684	-.04038	.015693	-.012731	-.04546	-.00292	.00987	.02526		
5.289	12.490	.00431	.00522	-.04229	.02941	-.03054	.13662	.00861	.00787	.02549		
5.289	20.818	.00526	.00540	-.04703	.04703	-.03554	.13191	.01581	.00231	.02477		
5.289	25.599	.00453	.00514	-.05464	.59194	-.03254	.12999	-.00799	.00681	.02589		
5.289	29.320	.00502	.00167	-.05891	.74804	-.04072	.12839	-.00577	.00682	.02547		
GRADIENT		.00000	.00000	-.00000	.02222	-.00588	-.00417	-.00417	-.00030	-.00000		

PARAMETRIC DATA

$ALPHA = .000$
 $ELEVON = .000$

RUDER = .000

CBL = .03494

PARAMETRIC DATA

$ALPHA = .000$
 $ELEVON = .000$

RUDER = .000

CBL = .03494

IA16 - ARC 3.5 191 - TANK

REFERENCE DATA

SURF = 2093.0000 Sq.FT. XRP = 979.0000 IN. XT
 LREF = 1293.3000 IN. YRP = .0000 IN YT
 BREF = 1293.3000 IN. ZRP = 400.0000 IN. ZT
 SCALE = .0100

RUN NO. 26/9 RVAL = 3.11 GRADIENT INTERVAL = -.00/ 5.00

MACH	ALPHA	CAB-T	QH	CR	CA	QM	QN	CR
5.289	-30.210	-.00198	.62224	.00023	.16971	.14777	-.00419	.00135
5.289	-21.625	.00171	.46356	.00079	.15468	.10440	-.00361	.00070
5.289	-20.401	.00097	.35976	-.00170	.13748	.06937	-.00277	.00044
5.289	-14.732	.00110	.22533	-.00416	.11650	.03484	-.00221	.00025
5.289	-10.179	.001679	.14289	-.00316	.10794	.01847	-.00165	.00019
5.289	-9.192	.001644	.11020	-.00476	.10497	.01341	-.00165	.00014
5.289	-8.129	.001578	.07929	-.00345	.10249	.01054	-.00147	.00002
5.289	-4.922	.001536	.03218	-.00355	.10153	.00867	-.00115	-.00001
5.289	-2.050	.001624	.02920	-.00725	.09992	.00781	-.00098	-.00003
5.289	.074	.001560	.00412	-.00801	.09846	.00686	-.00092	-.00002
5.289	2.185	.001628	.00328	-.00791	.09731	.00612	-.00082	-.00004
5.289	4.157	.001539	.00319	-.00884	.09548	.00589	-.00073	-.00003
5.289	6.164	.001667	.00637	-.00984	.09644	.00582	-.00068	-.00004
5.289	5.162	.001671	.00459	-.01058	.09846	.00469	-.00027	-.00004
		.00010	.01168	-.00035	-.00548	-.00007	.00011	-.00000

(X5506) (21 FEB 75)

PARAMETRIC DATA

DETA = .000
 DEVN = .000
 ELDEVN = .000
 RUDER = .000